# APPENDIX A

**Room Data Sheets** 

Building	Moodie I	LMSF Main	tenance B	uilding						
Room Name:	Comms/	PS&D Tech	nician Sho	р				Room Numb	er:	NA
ARCHITECT	URAL									
Function:	Worksho	p and Stora	ge	Net Area:	20	m2	Numb	er of Occupant	S:	3

Fire Rating: NA Barrier Free: Yes

**ROOM CHARACTERISTICS** 

Sound Control: Standard Special Ceiling

Conditions:

STC Rating: 45 Special Floor

Conditions

Other: - Special Wall Conditions :

**ROOM FINISHES** 

Floor: SC Base: RB Wall: PT

Ceiling: **NA** Millwork:

Doors (Size): 1800x2100 Type: Fire Rating: Hardware: Access Control

O/H Doors Type: - Fire Rating: - Hardware: -

(Size):

 Windows:
 Frame:
 Fire Rating:
 Glazing:

 Wind Screens:
 Frame:
 Fire Rating:
 Glazing:

Security Barriers: - Frame: - Fire Rating: - Glazing: -

**MILLWORK** 

Counter: - Matl: - Comment:

Shelving: - Matl: - Comment: -

FIXTURES: -

**EQUIPMENT**:

OTHER: First floor, direct access to main shop

**REMARKS**:

HVAC system: Standard office Air Supply: Standard Office

Min. # of air changes/hr.: - Air Exhaust: Ceiling

LAVS: - Number: - Fixture: - Water Closet: - Number: - Fixture: - Urinal: - Number: - Fixture: -

Drinking - Room Thermostat: **No** 

Fountain:

Floor Drain: Drain Type:

Other:

Comments:

**ELECTRICAL** 

Receptacles: Minimum 10 120VAC/15A duplex outlets at 1000mm AFF

Switches: Low Voltage - Dimmer

(Qty.): (Qty.):

Other: -

Emergency Lighting Required: All lighting on backup power (genset)

Lighting Type: LED Lighting Level (Lux): 500

Communications: Minimum 4 network data outlets

Fire Alarm to OBC3.2.4: P.A. System Coverage Yes

Required:

T.V. Outlet

(Qty.):

Telephone/Data Outlet (Qty.) (1) Wall mounted

Security Requirements: Provide access control hardware

A/V Systems:

Comments: Coordinate location of power/data outlets with RTG

**NOTES** 

Moodie LMSF Office Building	Moodie LMSF Maintenance Building				
Room Name:	Janitor's Closet			Room Number:	NA

**ARCHITECTURAL** 

Function: Janitor's Closet Net Area: 4 m2 Number of Occupants: NA

Fire Rating: NA Barrier Free: Yes

**ROOM CHARACTERISTICS** 

Sound Control: Standard Special Ceiling

Conditions:

STC Rating: 55 Special Floor

Conditions

Other: - Special Wall Conditions

**ROOM FINISHES** 

Floor: PCT Base: CT Wall: PT/1220mm CT Wainscot

Ceiling: LAT Millwork:

Doors (Size): 900x2100 Type: SC Fire Rating: Varies Hardware: Access Control;

O/H Doors Type: - Fire Rating: - Hardware: -

(Size):

Windows: Frame: - Fire Rating: - Glazing: - Wind Screens: - Frame: - Fire Rating: - Glazing: -

Security Barriers: - Frame: - Fire Rating: - Glazing: -

MIL<u>LWORK</u>

Counter: - Matl: Comment:

Shelving: Minimum Matl: SS Comment:

150 x450 (mm)

FIXTURES: One porcelain coated cast iron floor mounted janitorial sink, mop racks

EQUIPMENT: -

OTHER: -

REMARKS:

MECHANICAL

HVAC system: - Air Supply: Undercut door

Min. # of air changes/hr.: - Air Exhaust: 100%

LAVS: Janitorial Number: Min. Per Code Fixture: Water Closet: No Number: Min. Per Code Fixture: Urinal: No Number: -Min. Per Code Fixture: -

Drinking - Room Thermostat: **No** 

Fountain:

Floor Drain: 1 per every 25m² or portion thereof Drain Type: -

Other:

Comments: -

ELECTRICAL

Receptacles: 1 quad
Switches: Low Voltage - Dimmer

(Qty.): (Qty.): Other:

Emergency Lighting Required:

Lighting Type: LED Lighting Level (Lux): 300 -

Communications:

Fire Alarm to OBC3.2.4:

P.A. System Coverage

Yes

Required:

T.V. Outlet -

Telephone/Data Outlet (Qty.)

Security Requirements: Access Control

A/V Systems:

CAN\_DMS: \132040802\1

(Qty.):

Comments:

# **NOTES**

RFP: Request for Quotation
OESC: Ontario Electrical Safe Code

Hardware:

Hardware:

Latch

Building	Moodie LMSF Maintenance Building				
Room Name:	RTG Break Room			Room Number:	NA

**ARCHITECTURAL** 

Function: Break Room Net Area: 40 m2 Number of Occupants: 20

Fire Rating: NA Barrier Free: Yes

**ROOM CHARACTERISTICS** 

Sound Control: Standard Special Ceiling Conditions:
STC Rating: 45 Special Floor Conditions
Other: - Special Wall Conditions

**ROOM FINISHES** 

Floor: VCT Base: RB Wall: PT

Millwork:

Type:

Doors (Size): 900x2100 Type: Fire Rating: Per

code

O/H Doors (Size):

Ceiling:

Windows: Provide Frame: - Fire Rating: - Glazing: -

Fire Rating:

daylighting

LAT

Wind Screens: - Frame: - Fire Rating: - Glazing: -

Security Barriers: - Frame: - Fire Rating: - Glazing: -

<u>MILLWORK</u>

Counter: Kitchenette Matl: Solid Comment:

case work; surface at

kitchenette

Shelving: Single Matl: HPL Comment:

adjustable lowers two adjustable uppers

FIXTURES: Provide casework with stainless steel kitchen sink with waste disposer, countertop space sufficient for coffee

maker and microwave; full length overhead cabinets

Provide floor area, water, floor sink and electrical for not less than two vending machines

EQUIPMENT: Provide (1) 1220mm LCD monitor and connection to digital broadcast media (cable TV); microwave, coffee

maker, 480 litre frost free refrigerator-freezer.

OTHER: Providing seating and multiple tables for 20 (4-6 persons per table maximum).

**REMARKS:** 

MECHANICAL

HVAC system: Standard office Air Supply: Standard Office, Ceiling

Min. # of air changes/hr.: - Air Exhaust: Ceiling

LAVS: - Number: - Fixture: - Water Closet: - Number: - Fixture: - Urinal: - Number: - Fixture: -

Drinking - Room Thermostat: Yes

Fountain:

Floor Drain: Drain Type:

Other:

Comments:

**ELECTRICAL** 

Receptacles: Standard office

Switches: Low Voltage - Dimmer (Qty.): (Qty.):

Other: -

Emergency Lighting Required: All lighting on backup power (genset) and UPS

Lighting Type: LED room, LED under counter Lighting Level (Lux): 300 -

Communications:

Fire Alarm to OBC3.2.4: - P.A. System Coverage **Yes** 

Required:

T.V. Outlet Wall mounted

(Qty.):

Telephone/Data Outlet (Qty.) -1 wall mounted phone; 1 wall mounted at LCD monitor

Security Requirements:

A/V Systems: See above

Comments: -

**NOTES** 

Building	Moodie LMSF	Maintenance B	uilding						
Room Name:	Conference R	oom					Room Numb	er:	NA
ARCHITECTU	RAL								
Function:	RTG Conferen	ce Room	Net Area:	50	m2	Number	of Occupant	is:	10
Fire Rating:	NA		Barrier Free:	Yes					
ROOM CHARACT	ERISTICS								
Sound Control:	Standard	Special Ceil Conditions:	ing						
STC Rating:	45	Special Floo Conditions	r						
Other:	-	Special Wal	Conditions :						
ROOM FINISHES									
Floor:	VCT	Base:	RB	Wall:	PT				
Ceiling:	LAT	Millwork:							
Doors (Size):	900x2100	Type:		Fire Rating:			Hardware:	-	
O/H Doors		Type:	-	Fire Rating:	-		Hardware:	-	
(Size): Windows:		Frame:		Fire Rating:			Glazing:		
Wind Screens:	-	Frame:	-	Fire Rating:	•		Glazing:	-	
Security Barriers:	-	Frame:	•	Fire Rating:	-		Glazing:	-	
MILLWORK									
Counter:	_	Matl:	_	Comment:					
Shelving:	-	Matl:	-	Comment:	-				
FIXTURES:		er connection al	l walls; data and p	ower outlet flush	with flo	or centered	d on confere	nce ro	oom
	table								
EQUIPMENT:									
OTHER:									

Room shall be configured to seat 10 comfortably around a conference table with space to move behind

CAN\_DMS: \132040802\1

**REMARKS**:

seated occupants.

HVAC system: Standard office Air Supply: Standard Office, Ceiling

Min. # of air changes/hr.: - Air Exhaust: Ceiling

LAVS: - Number: - Fixture: - Water Closet: - Number: - Fixture: - Urinal: - Number: - Fixture: -

Drinking - Room Thermostat: Yes

Fountain:

Floor Drain: Drain Type:

Other:

Comments:

**ELECTRICAL** 

Receptacles: Minimum four outlets at workstation

Switches: Low Voltage - Dimmer Yes

(Qty.):

Other: -

Emergency Lighting Required: All lighting on backup power (genset)

Lighting Type: LED Lighting Level (Lux): 500

Communications:

Fire Alarm to OBC3.2.4: - P.A. System Coverage **Yes** 

Required:

T.V. Outlet Wall mounted

(Qty.):

Telephone/Data Outlet (Qty.) Standard plus data and power on one wall for connection to large format monitor.

Security Requirements: - A/V Systems: -

Comments: Lighting shall be arranged to enable dimming at media presentation wall (end wall relative to conference

table)

<u>NOTES</u>

Building	Moodie LMSF Maintenance Building				
Room Name:	Facility Maintenance Shop			Room Number:	NA

**ARCHITECTURAL** 

Workshop and Storage 20 Function: Net Area: m2 Number of Occupants: 3

NA Barrier Free: Yes Fire Rating:

**ROOM CHARACTERISTICS** 

Sound Control: Standard Special Ceiling

Conditions:

STC Rating: 45 Special Floor

Conditions

Other: Special Wall Conditions :

**ROOM FINISHES** 

SC RB PT, 1220mm painted 19mm plywood Floor: Base: Wall:

A/C exterior grade all walls or other impact resistant material of similar

performance

Ceiling: NA Millwork:

1800x2100 Fire Rating: Doors (Size): Type: Hardware: Access Control

to exterior and interior

Fire Rating: Type: Hardware:

O/H Doors (Size):

Windows: Frame: Fire Rating: Glazing:

Wind Screens: Frame: Fire Rating: Glazing: Security Barriers: Frame: Fire Rating: Glazing:

**MILLWORK** 

Comment: Counter: Matl:

Shelving: Matl: Comment:

FIXTURES:

**EQUIPMENT:** 

OTHER: Direct access to outside and interior

REMARKS: Lawn mowers, snow blowers, and other gas powered equipment to be stored in this room.

MECHANICAL

HVAC system: Standard office Air Supply: Standard Office

Min. # of air changes/hr.: - Air Exhaust: Ceiling

LAVS: - Number: - Fixture: - Water Closet: - Number: - Fixture: - Urinal: - Number: - Fixture: -

Drinking - Room Thermostat: **No** 

Fountain:

Floor Drain: Drain Type:

Other:

Comments:

ELECTRICAL

Receptacles: Minimum 10 120VAC/15A duplex outlets at 1000mm AFF for

Switches: Low Voltage - Dimmer (Qty.): (Qty.):

(Qty.):
Other:

Emergency Lighting Required: All lighting on backup power (genset)

Lighting Type: LED Lighting Level (Lux): 500

Communications: Minimum 4 network data outlets

Fire Alarm to OBC3.2.4: P.A. System Coverage Yes

Required:

T.V. Outlet

(Qty.):

Telephone/Data Outlet (Qty.) (1) Wall mounted

Security Requirements: Provide access control hardware

A/V Systems:

Comments: Coordinate location of power/data outlets with RTG

## **NOTES**

Building	Moodie LMSF Maintenance Building				
Room Name:	First Aid			Room Number:	NA

# ARCHITECTURAL

Function: Storage of First Aid Materials Net Area: 8 m2 Number of Occupants: NA

Fire Rating: NA Barrier Free: Yes

### **ROOM CHARACTERISTICS**

Sound Control: Standard Special Ceiling

Conditions:

STC Rating: 45 Special Floor Conditions

Other: - Special Wall Conditions :

#### **ROOM FINISHES**

Floor: VCT Base: RB Wall: PT

Ceiling: LAT Millwork:

Doors (Size): 900x2100 Type: Fire Rating: Hardware: Latch
O/H Doors Type: - Fire Rating: - Hardware: -

(Size):

Windows: - Frame: - Fire Rating: - Glazing: Wind Screens: - Frame: - Fire Rating: - Glazing: Security Barriers: - Frame: - Fire Rating: - Glazing: -

## **MILLWORK**

Counter: - Matl: - Comment: Shelving: - Matl: - Comment:

FIXTURES: -

**EQUIPMENT**:

OTHER:

REMARKS:

HVAC system: Standard office Air Supply: Standard Office, Ceiling

Min. # of air changes/hr.: - Air Exhaust: Ceiling

LAVS: - Number: - Fixture: - Water Closet: - Number: - Fixture: - Urinal: - Number: - Fixture: -

Drinking - Room Thermostat: **No** 

Fountain:

Floor Drain: Drain Type: -

Other:

Comments:

ELECTRICAL

Receptacles: Minimum four outlets at workstation

Switches: Low Voltage - Dimmer - (Qty.): (Qty.):

Other:

Emergency Lighting Required: All lighting on backup power (genset)

Lighting Type: LED Lighting Level (Lux): 200

Communications:

Fire Alarm to OBC3.2.4: P.A. System Coverage Yes

Required:

T.V. Outlet Wall mounted

(Qty.):

Telephone/Data Outlet (Qty.) 1

Security Requirements:

A/V Systems:

Comments: -

**NOTES** 

Building	Moodie Fin2L	Maintenance B	uilding				
Room Name:	Storage					Room Numl	ber: NA
ARCHITECTU	IRAL						
Function:	Storage of Office	ce Materials	Net Area:	8.6	m2	Number of Occupan	nts: NA
Fire Rating:	NA		Barrier Free:	Yes			
ROOM CHARAC	TERISTICS						
Sound Control:	Standard	Special Ceili	ing				
STC Rating:	45	Conditions: Special Floo Conditions	or				
Other:	-	Special Wall	Conditions :				
ROOM FINISHES	<u>S</u>						
Floor: Ceiling:	VCT LAT	Base: Millwork:	RB	Wall:	PT		
Doors (Size):	900x2100	Type:		Fire Rating:		Hardware:	Access Control
O/H Doors (Size):		Type:	-	Fire Rating:	-	Hardware:	-
Windows:	-	Frame:	-	Fire Rating:	-	Glazing:	-
Wind Screens:	-	Frame:	-	Fire Rating:	-	Glazing:	-
Security Barriers:	-	Frame:	•	Fire Rating:	-	Glazing:	•
<u>MILLWORK</u>							
Counter:	-	Matl:	-	Comment:			
Shelving:	•	Matl:	•	Comment:	-		
FIXTURES:	-						
EQUIPMENT:							
OTHER:							
OTTLEN.							
REMARKS:							

HVAC system: Standard office Air Supply: Standard Office, Ceiling

Min. # of air changes/hr.: - Air Exhaust: Ceiling

LAVS: - Number: - Fixture: - Water Closet: - Number: - Fixture: - Urinal: - Number: - Fixture: -

Drinking - Room Thermostat: **No** 

Fountain:

Floor Drain: Drain Type:

Other:

Comments:

**ELECTRICAL** 

Receptacles: Minimum four outlets at workstation

Switches: Low Voltage - Dimmer - (Qty.): (Qty.):

Other:

Emergency Lighting Required: All lighting on backup power (genset)

Lighting Type: LED Lighting Level (Lux): 300 -

Communications:

Fire Alarm to OBC3.2.4: P.A. System Coverage Yes

Required:

T.V. Outlet Wall mounted

(Qty.):

Telephone/Data Outlet (Qty.) Standard

Security Requirements: Provide access control hardware

A/V Systems:

Comments: -

**NOTES** 

Building	Moodie LMSF Maintenance Building			

Room Name:	Open Office							Room Numb	er: NA
ARCHITECTUR	RAL								
Function:	RTG Open Office		Net Area:		50	m2	Numbe	er of Occupant	ts: <b>6</b>
Fire Rating:	NA		Barrier Fr	ee:	Yes				
ROOM CHARACT Sound Control:	<u>ERISTICS</u> Standard	Special Ceiling	1						
		Conditions:	ı						
STC Rating:	45	Special Floor Conditions							
Other:	-	Special Wall C	onditions	:					
ROOM FINISHES									
Floor:	VCT	Base:	RB		Wall:	PT			
Ceiling:	LAT	Millwork:			Cina Datinas			Handwana	A
Doors (Size):	900x2100	Type:			Fire Rating:			Hardware:	Access Control
O/H Doors (Size):		Type:	-		Fire Rating:	-		Hardware:	-
(Size). Windows:	Required	Frame:	-		Fire Rating:	-		Glazing:	-
Wind Screens:	-	Frame:	-		Fire Rating:	-		Glazing:	-
Security Barriers:	-	Frame:	-		Fire Rating:	-		Glazing:	-
MILLWORK									
Counter:	-	Matl:	-		Comment:				
Shelving:	-	Matl:	-		Comment:	-			
FIXTURES:	(6) 5m2 office cub								
	under cabinet ligl integral with syst								ounter,
	Data and power c	onnection for o	office copi	er/printer					
EQUIPMENT:									
OTHER:									
OTTIER.									
REMARKS:	In suite with Supe	ervisor's Office							
CAN DMS: \132040	802\1								

HVAC system: Standard office Air Supply: Standard Office, Ceiling

Min. # of air changes/hr.: - Air Exhaust: Ceiling

LAVS: - Number: - Fixture: - Water Closet: - Number: - Fixture: - Urinal: - Number: - Fixture: -

Drinking - Room Thermostat: Yes

Fountain:

Floor Drain: Drain Type:

Other:

Comments:

**ELECTRICAL** 

Receptacles: Minimum four outlets at workstation

Switches: Low Voltage - Dimmer Yes

(Qty.):

Other: -

Emergency Lighting Required: All lighting on backup power (genset)

Lighting Type: LED Lighting Level (Lux): 500

Communications:

Fire Alarm to OBC3.2.4: P.A. System Coverage Yes

Required:

T.V. Outlet

(Qty.):

Telephone/Data Outlet (Qty.) Standard plus data and power for each cubicle

Security Requirements: Access Control

A/V Systems:

Comments: -

**NOTES** 

Building	Moodie LMSF	Maintenance Bui	lding						
Room Name:	Quiet Room						Room Numb	per: I	NA
ARCHITECTU	JRAL								
Function:	Quite Room fo	r RTG	Net Area:	8	m2	Numb	er of Occupan	ts: 2	2
Fire Rating:	NA		Barrier Free:	Yes					
ROOM CHARAC									
Sound Control:	Standard	Special Ceiling Conditions:	g						
STC Rating:	45	Special Floor Conditions							
Other:	-	Special Wall C	Conditions :						
ROOM FINISHES									
Floor:	CPT	Base:	RB	Wall:	PT				
Ceiling:	LAT 900x2100	Millwork:		Eiro Doting:			Hardware:	Latch	
Doors (Size): O/H Doors	900X2100	Type: Type:	_	Fire Rating: Fire Rating:	-		Hardware:	Laten	
(Size):		Type.	-	i ile rading.	-		riaidwaie.	-	
Windows:	-	Frame:	-	Fire Rating:	•		Glazing:	-	
Wind Screens:	-	Frame:	-	Fire Rating:	-		Glazing:	-	
Security Barriers:	-	Frame:	-	Fire Rating:	-		Glazing:	-	
MILLWORK Counter:		Math		Comment:					
Counter: Shelving:	•	Matl: Matl:	•	Comment:	_				
-	•	Mali.	•	Comment.	-				
FIXTURES:	-								
EQUIPMENT:									
OTHER:									
REMARKS:									

HVAC system: Standard office Air Supply: Standard Office, Ceiling

Min. # of air changes/hr.: - Air Exhaust: Ceiling

LAVS: - Number: - Fixture: - Water Closet: - Number: - Fixture: - Urinal: - Number: - Fixture: -

Drinking - Room Thermostat: Yes

Fountain:

Floor Drain: Drain Type: -

Other:

Comments:

ELECTRICAL

Receptacles: Minimum four outlets

Switches: Low Voltage - Dimmer Yes

(Qty.):

Other: -

Emergency Lighting Required: All lighting on backup power (genset)

Lighting Type: LED Lighting Level (Lux): 500

Communications:

Fire Alarm to OBC3.2.4: P.A. System Coverage Yes

Required:

(Qty.):

T.V. Outlet

(Qty.):

Telephone/Data Outlet (Qty.) 2
Security Requirements: -

A/V Systems:

Comments: -

**NOTES** 

1-hr

Building	Moodie LMSF	Maintenance	Building					
Room Name:	RTG Server R	oom					Room Number:	NA
ARCHITECT	JRAL							
Function:	RTG Compute	r Equip.	Net Area:	8.6	m2	Numb	er of Occupants:	1

Barrier Free:

Yes

**ROOM CHARACTERISTICS** 

Sound Control: Standard Special Ceiling

Conditions:

STC Rating: 55 Special Floor Antistatic floor

Conditions

Other: - Special Wall Conditions

**ROOM FINISHES** 

Fire Rating:

RB Floor: **RAF** Wall: Base: PT/minimum 10m<sup>2</sup> comm. backboard Ceiling: LAT Millwork: Doors (Size): 900x2100 Type: Fire Rating: 20 Hardware: **Access** Control O/H Doors Type: Fire Rating: Hardware: (Size): Windows: Frame: Fire Rating: Glazing: Wind Screens: Frame: Fire Rating: Glazing: Glazing: Security Barriers: Frame: Fire Rating:

**MILLWORK** 

Counter: - Matl: Comment: Shelving: - Matl: Comment:

FIXTURES: -

EQUIPMENT: Assume two standard, full height server racks; must be accessible front and back

OTHER: -

REMARKS: -

HVAC system: 3x Redundant Data Center Type Air Supply: Below floor (see comments)

Min. # of air changes/hr.: - Air Exhaust: Ceiling

LAVS: - Number: - Fixture: - Water Closet: - Number: - Fixture: - Urinal: - Number: - Fixture: -

Drinking - Room Thermostat: -

Fountain:

Floor Drain: Drain Type:

Other: Provide clean agent and pre-action fire sprinkler system.

Comments: Provide minimum 3-tons HVAC. System shall be on emergency backup power (genset). Volume shall be

controllable at each diffuser.

**ELECTRICAL** 

Receptacles: On emergency backup power

Switches: Low Voltage - Dimmer (Qty.): (Qty.):

Other:

Emergency Lighting Required: All lighting on backup power (genset) and UPS

Lighting Type: LED Lighting Level (Lux): 500

.

Communications: Tie to OC Transpo [REDACTED]

Fire Alarm to OBC3.2.4: - P.A. System Coverage Yes

Required:

T.V. Outlet

(Qtv.):

Telephone/Data Outlet (Qty.)

Security Requirements: Provide access control hardware

A/V Systems:

Comments: Fire stop all conduit

**NOTES** 

RFP: Request for Quotation CAN DMS: \132040802\1

OESC: Ontario Electrical Safe Code

Building	Moodie LMSF	Maintenance Bu	ilding				
Room Name:	Storage					Room Numbe	r: N
ARCHITECTU	RAL						
Function:	Storage		Net Area:	20	m2	Number of Occupants	: N.
Fire Rating:	NA		Barrier Free:	Yes			
ROOM CHARACT	TERISTICS						
Sound Control:	Standard	Special Ceilin Conditions:	ng				
STC Rating:	45	Special Floor Conditions					
Other:	-	Special Wall	Conditions :				
ROOM FINISHES							
Floor:	VCT	Base:	RB	Wall:	PT		
Ceiling:	LAT	Millwork:		E' D "			
Doors (Size):	900x2100	Type:		Fire Rating:			Access Control
O/H Doors (Size):		Type:	-	Fire Rating:	•		-
Windows:	-	Frame:	-	Fire Rating:	-	Glazing:	-
Wind Screens:	-	Frame:	-	Fire Rating:	-	Glazing:	-
Security Barriers:	•	Frame:	-	Fire Rating:	-	Glazing:	-
MILLWORK							
Counter:	-	Matl:	-	Comment:			
Shelving:	-	Matl:	-	Comment:	-		
FIXTURES:							
EQUIPMENT:							
OTHER:	Heavy duty in	dustrial shalving	min 500 kg/m²: 6	00mm doon min	100 lm	; brace at floor and floor	dook
<b>○</b> 111 <b>⊏</b> 13.	above	aasiiai siiciviily,	500 kg/III⁻, 0	оонин исср, пШ	. 100 1111	, mace at noor and noor	ucch
REMARKS:							

HVAC system: Standard office Air Supply: Standard Office, Ceiling

Min. # of air changes/hr.: - Air Exhaust: Ceiling

LAVS: - Number: - Fixture: - Water Closet: - Number: - Fixture: - Urinal: - Number: - Fixture: -

Drinking - Room Thermostat: **No** 

Fountain:

Floor Drain: Drain Type:

Other:

Comments:

**ELECTRICAL** 

Receptacles: Minimum four outlets at workstation

Switches: Low Voltage - Dimmer - (Qty.): (Qty.):

Other: -

Emergency Lighting Required: All lighting on backup power (genset)

Lighting Type: LED Lighting Level (Lux): 300

Communications:

Fire Alarm to OBC3.2.4: P.A. System Coverage Yes

Required:

T.V. Outlet

(Qty.):

Telephone/Data Outlet (Qty.) 1 wall mounted

Security Requirements: Provide access control hardware

A/V Systems:

Comments: -

**NOTES** 

Building	Moodie LMSF Maintenance Building			

Room Name:	Office						Room Number:		NA
ARCHITECTUI	RAL								
Function:	Supervisor Office		Net Area:	19	m2	Numbe	er of Occupant	is:	1
Fire Rating:	NA		Barrier Free:	Yes					
ROOM CHARACT	ERISTICS								
Sound Control:	Standard	Special Ceiling Conditions:	)						
STC Rating:	45	Special Floor Conditions							
Other:	-	Special Wall C	conditions :						
ROOM FINISHES	ODT	Danas	DD.	\ <b>\</b> /_II.	DT				
Floor: Ceiling:	CPT LAT	Base: Millwork:	RB	Wall:	PT				
Doors (Size):	900x2100	Type:		Fire Rating:			Hardware:	Lock	(
O/H Doors (Size):		Type:	-	Fire Rating:	-		Hardware:	-	
Windows:	Preferred	Frame:	-	Fire Rating:	-		Glazing:	-	
Wind Screens:	-	Frame:	-	Fire Rating:	-		Glazing:	-	
Security Barriers:	-	Frame:	-	Fire Rating:	-		Glazing:	-	
<u>MILLWORK</u>									
Counter:	•	Matl:	-	Comment:					
Shelving:	-	Matl:	-	Comment:	-				
FIXTURES:	•								
EQUIPMENT:									
OTHER:									
REMARKS:	All Project Co co					n. Provid	le desk, cred	enza, l	book

HVAC system: Standard office Air Supply: Standard Office, Ceiling

Min. # of air changes/hr.: - Air Exhaust: Ceiling

LAVS: - Number: - Fixture: - Water Closet: - Number: - Fixture: - Urinal: - Number: - Fixture: -

Drinking - Room Thermostat: Yes

Fountain:

Floor Drain: Drain Type: -

Other:

Comments:

**ELECTRICAL** 

Receptacles: Minimum four outlets at workstation

Switches: Low Voltage - Dimmer -

(Qty.): (Qty.):

Other: -

Emergency Lighting Required: All lighting on backup power (genset)

Lighting Type: LED Lighting Level (Lux): 500

Communications: Minimum 4 network data outlets

Fire Alarm to OBC3.2.4:

P.A. System Coverage Required:

system

Via phone system

only

T.V. Outlet Wall mounted

(Qty.):

Telephone/Data Outlet (Qty.) Standard

Security Requirements: Provide access control hardware

A/V Systems:

Comments: -

NOTES

Building	Moodie LMSF Maintenance Building				
Room Name:	Typical Multiple-Occupant Washroom			Room Number:	NA

## **ARCHITECTURAL**

Function: Wash/Locker/Shower Room Net Area: 45 m2 Number of Occupants: Varies

Fire Rating: NA Barrier Free: Yes

**ROOM CHARACTERISTICS** 

Sound Control: Standard Special Ceiling

Conditions:

STC Rating: 55 Special Floor

Conditions

Other: - Special Wall Conditions :

**ROOM FINISHES** 

Floor: PCT Base: CT Wall: PT/1220mm CT Wainscot

Ceiling: LAT Millwork:

Doors (Size): 900x2100 Type: SC Fire Rating: Varies Hardware: Class/Self Closing

O/H Doors Type: - Fire Rating: - Hardware: -

(Size):

Windows: Frame: - Fire Rating: - Glazing: - Wind Screens: - Frame: - Fire Rating: - Glazing: -

Security Barriers: - Frame: - Fire Rating: - Glazing: -

**MILLWORK** 

Counter: - Matl: Comment:

Shelving: Minimum Matl: SS Comment: Above urinals, water closets, lavatories

150 x450 (mm)

FIXTURES:

As required by code but not less than one urinal and one toilet per men's washroom and two toilets per women's wash room. Washrooms shall have not less than two lavatories. Provide stainless steel shelving above all fixtures

### Stainless steel washroom accessories:

- Toilet stalls (each): recessed or semi recessed toilet tissue dispenser, two roll; seat cover dispenser, accessibility accessories as required;
- Lavatories (for every two, but not less than one each): recessed or semi-recessed C-fold paper towel dispensers and waste receptacle;
- Other: electric high velocity hand drier
- . Shower stall (each): mirror, wooden bench with stainless steel legs two clothes hooks

EQUIPMENT: Furnish painted metal lockers including those as required for accessibility. Provide a minimum of 12 lockers

for women and 24 men Provide benches where required for accessibility. Lockers shall be 305mm x 610mm, with sloped tops and 150mm high based faced in tile matching floor finish. Locker rooms shall be sized to accommodate the maximum number of lockers required for ultimate system capacity or the design shall provide for contiguous enlargement of the locker room in a logical fashion that does not disrupt other

necessary facility functions

OTHER: Shower rooms shall be provided in the main wash rooms/locker rooms serving RTG maintenance crews.

Floors shall be PCT, walls full height CT. Showers shall be individual occupancy with a lockable door and

may be accessed independently from wash rooms.

Provide niche for clean linen (uniform) delivery storage and dirty linen disposal bins

REMARKS: Provide one men's and one women's wash/shower/locker room

**MECHANICAL** 

HVAC system: - Air Supply:

Min. # of air changes/hr.: - Air Exhaust:

LAVS: Yes Number: Min. Per Code Fixture: Water Closet: Yes Number: Min. Per Code Fixture: Urinal: Yes Number: -Min. Per Code Fixture: -

Drinking - Room Thermostat: **No** 

Fountain:

Floor Drain: 1 per every 25m<sup>2</sup> or portion thereof Drain Type: -

Other:

Comments: Shower rooms shall have 100% exhaust air

**ELECTRICAL** 

Receptacles: 1 per lavatory and shower stall

Switches: Low Voltage - Dimmer (Qty.): (Qty.):

(Qty.): Other:

**Emergency Lighting Required:** 

Lighting Type: LED Lighting Level (Lux): 200

-

Communications:

Fire Alarm to OBC3.2.4:

P.A. System Coverage Required:

T.V. Outlet

(Qty.):

Telephone/Data Outlet (Qty.) Security Requirements: A/V Systems: -

Comments: -

### **NOTES**

RFP: Request for Quotation

OESC: Ontario Electrical Safe Code

Moodie LMSF Office Building	Moodie LMSF Maintenance Building				
Room Name:	Typical Single Occupant Washroom			Room Number:	NA

Function: Washroom Net Area: 6 m2 Number of Occupants: NA

Fire Rating: NA Barrier Free: Yes

**ROOM CHARACTERISTICS** 

Sound Control: Standard Special Ceiling

Conditions:

STC Rating: 55 Special Floor

Conditions

Other: - Special Wall Conditions

**ROOM FINISHES** 

Floor: PCT Base: CT Wall: PT/1220mm CT Wainscot

Ceiling: LAT Millwork:

Doors (Size): 900x2100 Type: SC Fire Rating: Varies Hardware: Access Control;

Self-Closing

O/H Doors Type: - Fire Rating: - Hardware: -

(Size):

Windows:Frame:-Fire Rating:-Glazing:-Wind Screens:-Frame:-Fire Rating:-Glazing:-Security Barriers:-Frame:-Fire Rating:-Glazing:-

**MILLWORK** 

Counter: - Matl: Comment:

Shelving: Minimum Matl: SS Comment: Above urinals, water closets, lavatories

150 x450 (mm)

FIXTURES: One lavatory and one toilet per wash room

Stainless steel washroom accessories:

- Recessed or semi recessed toilet tissue dispenser, two roll; seat cover dispenser, accessibility accessories as required;
- Recessed or semi-recessed C-fold paper towel dispensers and waste receptacle;
- Other: electric high velocity hand drier

EQUIPMENT: -

OTHER:

**REMARKS**:

MECHANICAL

HVAC system: Air Supply:

Min. # of air changes/hr.: Air Exhaust:

LAVS: Yes Number: Min. Per Code Fixture: Water Closet: Yes Number: Min. Per Code Fixture: Urinal: No Number: -Min. Per Code Fixture:

Drinking Room Thermostat:

Fountain:

Floor Drain: 1 per every 25m<sup>2</sup> or portion thereof Drain Type:

Other:

Comments:

ELECTRICAL

Receptacles: 1 per lavatory

Switches: Low Voltage Dimmer (Qty.): (Qty.):

Other:

**Emergency Lighting Required:** 

Lighting Type: **LED** Lighting Level (Lux): 200

Communications:

Fire Alarm to OBC3.2.4: P.A. System Coverage Yes

Required:

T.V. Outlet (Qty.):

Telephone/Data Outlet (Qty.) Security Requirements: A/V Systems: -

Comments: -

### **NOTES**

RFP: Request for Quotation

OESC: Ontario Electrical Safe Code

Building	Moodie LMSF Maintenance Building				
Room Name:	Vehicle Maintenance Shop			Room Number:	NA

Function: Workshop and Storage Net Area: 30 m2 Number of Occupants: 4

Fire Rating: NA Barrier Free: Yes

**ROOM CHARACTERISTICS** 

Sound Control: Standard Special Ceiling

Conditions:

STC Rating: 45 Special Floor

Conditions

Other: - Special Wall Conditions :

**ROOM FINISHES** 

Floor: SC Base: RB Wall: PT, 1220mm painted 19mm plywood

A/C exterior grade all walls or other impact resistant material of similar

performance

Ceiling: NA Millwork:

Doors (Size): 1800x2100 Type: Fire Rating: Hardware: Access Control

Fire Rating:

Hardware: -

O/H Doors (Size):

Windows: - Frame: - Fire Rating: - Glazing: -

Wind Screens: - Frame: - Fire Rating: - Glazing: - Security Barriers: - Frame: - Fire Rating: - Glazing: -

**MILLWORK** 

Counter: - Matl: - Comment:

Type:

Shelving: - Matl: - Comment: -

FIXTURES: -

**EQUIPMENT**:

OTHER: First floor, direct access to main shop

**REMARKS:** 

MECHANICAL

HVAC system: Standard office Air Supply: Standard Office

Min. # of air changes/hr.: - Air Exhaust: Ceiling

LAVS: - Number: - Fixture: - Water Closet: - Number: - Fixture: - Urinal: - Number: - Fixture: -

Drinking - Room Thermostat: **No** 

Fountain:

Floor Drain: Drain Type:

Other:

Comments:

ELECTRICAL

Receptacles: Minimum 10 120VAC/15A duplex outlets at 1000mm AFF

Switches: Low Voltage - Dimmer

(Qty.): (Qty.):

Other: -

Emergency Lighting Required: All lighting on backup power (genset)

Lighting Type: LED Lighting Level (Lux): 500

Communications: Minimum 4 network data outlets

Fire Alarm to OBC3.2.4: P.A. System Coverage Yes

Required:

T.V. Outlet

(Qty.):

Telephone/Data Outlet (Qty.) (1) Wall mounted

Security Requirements: Provide access control hardware

A/V Systems:

Comments: Coordinate location of power/data outlets with RTG

**NOTES** 

Building	Moodie LMSF	Maintenance B	uilding				
Room Name:	Phase 1 Shop	Storage				Room Num	ber: N
ARCHITECTUI	RAL						
Function:	Storage		Net Area:	90	m <sup>2</sup>	Number of Occupar	nts: N
Fire Rating:	NA		Barrier Free:	Yes			
ROOM CHARACT	ERISTICS						
Sound Control:	Standard	Special Ceili Conditions:	ng				
STC Rating:	45	Special Floo Conditions	r				
Other:	-	Special Wall	Conditions :				
ROOM FINISHES							
Floor:	SC	Base:		Wall:	PT		
Ceiling:	NA	Millwork:		E. 5			
Doors (Size):	900x2100	Type:		Fire Rating:		Hardware:	Access Contro
O/H Doors (Size):		Type:	-	Fire Rating:	-	Hardware:	-
Windows:	-	Frame:	-	Fire Rating:	-	Glazing:	-
Wind Screens:	-	Frame:	-	Fire Rating:	-	Glazing:	-
Security Barriers:	-	Frame:	-	Fire Rating:	-	Glazing:	-
<u>MILLWORK</u>							
Counter:	-	Matl:	-	Comment:			
Shelving:	-	Matl:	-	Comment:	-		
FIXTURES:	-						
EQUIPMENT:							
OTHER:	Heavy duty na	allat rack shelvin	a min 500 ka/m²·	600mm deen mi	n 200 In	n; brace at floor and fl	oor deck

CAN\_DMS: \132040802\1

REMARKS:

MECHANICAL

HVAC system: Heat and ventilation only Air Supply: Standard Office, Ceiling

Min. # of air changes/hr.: - Air Exhaust: Ceiling

LAVS: - Number: - Fixture: - Water Closet: - Number: - Fixture: - Urinal: - Number: - Fixture: -

Drinking - Room Thermostat: **No** 

Fountain:

Floor Drain: Drain Type:

Other:

Comments:

**ELECTRICAL** 

Receptacles: Minimum four outlets at workstation; every 6,000mm along walls

Switches: Low Voltage - Dimmer (Qty.): (Qty.):

Other: -

Emergency Lighting Required: All lighting on backup power (genset)

Lighting Type: LED Lighting Level (Lux): 300

Communications:

Fire Alarm to OBC3.2.4: P.A. System Coverage Yes

Required:

T.V. Outlet

(Qty.):

Telephone/Data Outlet (Qty.) 1 wall mounted

Security Requirements: Provide access control hardware

A/V Systems:

Comments: -

**NOTES** 

Building	Moodie LMSF Maintenance Building				
Room Name:	Phase 2 & 3 Shop Storage			Room Number:	NA

Function: Storage Net Area: 300 m<sup>2</sup> Number of Occupants: NA

Fire Rating: NA Barrier Free: Yes

**ROOM CHARACTERISTICS** 

Sound Control: Standard Special Ceiling

Conditions:

STC Rating: 45 Special Floor

Conditions

Other: - Special Wall Conditions :

**ROOM FINISHES** 

Floor: SC Base: Wall: PT

Ceiling: NA Millwork:

Doors (Size): 900x2100 Type: Fire Rating: Hardware: Access Control

O/H Doors 3660x3660 Type: - Fire Rating: - Hardware: -

(Size): min.

Windows: - Frame: - Fire Rating: - Glazing: - Wind Screens: - Frame: - Fire Rating: - Glazing: -

Security Barriers: - Frame: - Fire Rating: - Glazing: - Glazing: -

**MILLWORK** 

Counter: - Matl: - Comment:

Shelving: - Matl: - Comment: -

FIXTURES: -

**EQUIPMENT**:

OTHER: Heavy duty industrial pallet rack shelving, min 500 kg/m<sup>2</sup>; 600mm deep, min. 400 lm; brace at floor and

floor deck above

REMARKS: Provide 200m<sup>2</sup> storage on ground floor and 100m<sup>2</sup> on mezzanine; mezzanine shall be accessible with

monorail crane from adjacent light maintenance track.

MECHANICAL

HVAC system: Heat and ventilation only Air Supply: Standard Office, Ceiling

Min. # of air changes/hr.: - Air Exhaust: Ceiling

LAVS: - Number: - Fixture: - Water Closet: - Number: - Fixture: - Urinal: - Number: - Fixture: -

Drinking - Room Thermostat: **No** 

Fountain:

Floor Drain: Drain Type:

Other:

Comments:

**ELECTRICAL** 

Receptacles: Minimum four outlets at workstation; every 6,000mm along walls

Switches: Low Voltage - Dimmer (Qty.): (Qty.):

Other: -

Emergency Lighting Required: All lighting on backup power (genset)

Lighting Type: LED Lighting Level (Lux): 300

Communications:

Fire Alarm to OBC3.2.4: P.A. System Coverage Yes

Required:

T.V. Outlet

(Qty.):

Telephone/Data Outlet (Qty.) 1 wall mounted

Security Requirements: Provide access control hardware

A/V Systems:

Comments: -

**NOTES** 

Moodie LM Office Building	ISF I	Moodie LMSF Office Building				
Room Name:		Janitor's Closet			Room Number:	NA

Function: Janitor's Closet Net Area: 4 m2 Number of Occupants: NA

Fire Rating: NA Barrier Free: Yes

**ROOM CHARACTERISTICS** 

Sound Control: Standard Special Ceiling

Conditions:

STC Rating: 55 Special Floor

Conditions

Other: - Special Wall Conditions :

**ROOM FINISHES** 

Floor: PCT Base: CT Wall: PT/1220mm CT Wainscot

Ceiling: LAT Millwork:

Doors (Size): 900x2100 Type: SC Fire Rating: Varies Hardware: Access Control;

O/H Doors Type: - Fire Rating: - Hardware: -

(Size):

 Windows:
 Frame:
 Fire Rating:
 Glazing:

 Wind Screens:
 Frame:
 Fire Rating:
 Glazing:

Security Barriers: - Frame: - Fire Rating: - Glazing: -

**MILLWORK** 

Counter: - Matl: Comment:

Shelving: Minimum Matl: SS Comment:

150 x450 (mm)

FIXTURES: One porcelain coated cast iron floor mounted janitorial sink, mop racks

EQUIPMENT: -

OTHER: -

REMARKS:

MECHANICAL

HVAC system: - Air Supply: Undercut door

Min. # of air changes/hr.: - Air Exhaust: 100%

LAVS: Janitorial Number: Min. Per Code Fixture: Water Closet: No Number: Min. Per Code Fixture: Urinal: No Number: -Min. Per Code Fixture: -

Drinking - Room Thermostat: **No** 

Fountain:

Floor Drain: 1 per every 25m² or portion thereof Drain Type: -

Other:

Comments: -

ELECTRICAL

Receptacles: 1 quad

Switches: Low Voltage - Dimmer

(Qty.): (Qty.):

Emergency Lighting Required:

Lighting Type: LED Lighting Level (Lux): 300 -

Communications:

Fire Alarm to OBC3.2.4:

P.A. System Coverage

Yes

Fire Alarm to OBC3.2.4:

P.A. System Coverage
Required:

T.V. Outlet

(Qty.):

Telephone/Data Outlet (Qty.)

Security Requirements: Access Control

A/V Systems:

Comments:

# **NOTES**

RFP: Request for Quotation
OESC: Ontario Electrical Safe Code

Building	Moodie LMSF Office Building				
Room Name:	Operator's Locker/Break/Day Room			Room Number:	NA

Function: Waiting Room for Transportation Net Area: 55 m2 Number of Occupants: 16

Crews

Fire Rating: NA Barrier Free: Yes

**ROOM CHARACTERISTICS** 

Sound Control: Standard Special Ceiling Conditions:

STC Rating: 45 Special Floor Conditions

Other: - Special Wall Conditions :

**ROOM FINISHES** 

Floor: VCT Base: RB Wall: PT Ceiling: LAT Millwork:

Doors (Size): 900x2100 Type: Fire Rating: Per Hardware: Latch

O/H Doors Type: - Fire Rating: -

(Size):

Windows: Provide Frame: - Fire Rating: - Glazing: -

 daylighting

 Wind Screens: Frame: Fire Rating: Glazing:

Security Barriers: - Frame: - Fire Rating: - Glazing: -

**MILLWORK** 

Shelving:

Counter: Kitchenette Matl: HPL at Comment:

case work; computer;
Computer solid
station surface at
kitchenette

Kitchenette

adjustable uppers

Single Matl: HPL Comment: adjustable lowers two

FIXTURES: Furnish painted metal lockers including those as required for accessibility. Provide benches where required

for accessibility. Lockers shall be size in accordance with the City of Ottawa Standards for Interior Design and

shall be provided in sufficient number at each location for opening day of service needs.

Provide floor area, water, floor sink and electrical for not less than two vending machines

EQUIPMENT: Provide (1) 1220mm LCD monitor and connection to digital broadcast media (cable TV).

CAN DMS: \132040802\1

Hardware:

OTHER: Seating at table for not less than eight, with full room capacity of not less than 16. Provide minimum two

computer workstations for crews, min. 900mm wide x 900mm deep work station (seated) with side vision

screens (carrel set-up).

REMARKS: Network connectivity and power to be provided at workstations

MECHANICAL

HVAC system: Standard office Air Supply: Standard Office, Ceiling

Min. # of air changes/hr.: - Air Exhaust: Ceiling

LAVS: - Number: - Fixture: - Water Closet: - Number: - Fixture: - Urinal: - Number: - Fixture: -

Drinking - Room Thermostat: Yes

Fountain:

Floor Drain: Drain Type: -

Other:

Comments:

**ELECTRICAL** 

Receptacles: Standard office, at ea. comp. station, and at counter

Switches: Low Voltage - Dimmer (Qty.): (Qty.):

Other: -

Emergency Lighting Required: All lighting on backup power (genset) and UPS

Lighting Type: LED Lighting Level (Lux): 200

Communications:

Fire Alarm to OBC3.2.4: - P.A. System Coverage **Yes** 

Required:

T.V. Outlet Wall mounted

(Qty.):

Telephone/Data Outlet (Qty.) - Standard; 2 computer

Security Requirements:

A/V Systems: See above

Comments: -

**NOTES** 

Building	Moodie LMSF Office Building				
Room Name:	Operator's Lunch Room			Room Number:	NA

Function: Lunch Room for Transportation Net Area:

33 m2 Number of Occupants:

Crews

Fire Rating: NA Barrier Free: Yes

**ROOM CHARACTERISTICS** 

Sound Control: Standard STC Rating: 45

**Special Ceiling Conditions: Special Floor Conditions Special Wall Conditions** 

**ROOM FINISHES** 

Other:

Floor: **VCT** Ceiling: LAT

RB

Wall:

PT

Millwork: Doors (Size): 900x2100 Type:

Base:

Type:

Matl:

Matl:

Fire Rating: Fire Rating: Per code Hardware: Latch

O/H Doors (Size):

**Provide** 

Fire Rating:

Glazing:

Hardware:

Windows:

daylighting

Frame:

Fire Rating:

Glazing:

Wind Screens: Security Barriers: Frame: Frame:

Fire Rating:

Glazing:

**MILLWORK** 

Counter:

Kitchenette case work;

solid surface Comment:

Computer

station

Shelving: Single

adjustable lowers two adjustable uppers

HPL

Comment:

FIXTURES:

Provide casework with stainless steel kitchen sink with waste disposer, countertop space sufficient for coffee maker and microwave plus 100% linear open; full length overhead cabinets

Provide floor area, water, floor sink and electrical for not less than two vending machines

**EQUIPMENT**: Provide microwave, coffee maker, 480 litre frost free refrigerator-freezer

OTHER: Seating at table for not less than six, with full room capacity of not less than 8.

**REMARKS:** 

MECHANICAL

HVAC system: Standard office Air Supply: Standard Office, Ceiling

Min. # of air changes/hr.: - Air Exhaust: Ceiling

LAVS: - Number: - Fixture: - Water Closet: - Number: - Fixture: - Urinal: - Number: - Fixture: -

Drinking - Room Thermostat: Yes

Fountain:

Floor Drain: Drain Type: -

Other:

Comments:

ELECTRICAL

Receptacles: Standard office and at counter

Switches: Low Voltage - Dimmer (Qty.): (Qty.):

Other: -

Emergency Lighting Required: All lighting on backup power (genset) and UPS

Lighting Type: LED Lighting Level (Lux): 200

Communications:

Fire Alarm to OBC3.2.4: - P.A. System Coverage **Yes** 

Required:

T.V. Outlet Wall mounted

(Qty.):

Telephone/Data Outlet (Qty.) - Standard

Security Requirements:

A/V Systems: See above

Comments: -

**NOTES** 

Building	Moodie LMSF	Office Building							
Room Name:	Open Office						Room Numb	oer:	N.
ARCHITECTU	RAL								
Function:	OC Transpo Ope	en Office	Net Area:	50	m <sup>2</sup>	Numbe	er of Occupan	ts:	5
Fire Rating:	NA		Barrier Free:	Yes					
ROOM CHARACT	TERISTICS								
Sound Control:	Standard	Special Ceiling Conditions:	g						
STC Rating:	45	Special Floor Conditions							
Other:	-	Special Wall C	Conditions :						
ROOM FINISHES									
Floor:	VCT	Base:	RB	Wall:	PT				
Ceiling:	LAT	Millwork:						_	
Doors (Size):	900x2100	Type:		Fire Rating:			Hardware:	Acc Con	
O/H Doors (Size):		Type:	-	Fire Rating:	-		Hardware:	-	
Windows:	Required	Frame:	•	Fire Rating:	-		Glazing:	-	
Wind Screens:	-	Frame:	-	Fire Rating:	-		Glazing:	-	
Security Barriers:	-	Frame:	-	Fire Rating:	-		Glazing:	-	
MILLWORK									
Counter:	-	Matl:	-	Comment:					
Shelving: FIXTURES:	- (5) 7 5m2 office	Matl:	" shaned work	Comment: surfaces, (2) two-	- drawer n	nedestals	full upper ca	hinet	s wi
	under cabinet li	ghting; 1 task ch	nair per cubicle	; 1 data and 4 dup on on open side an	lex powe	er connec	tions below o		
	Data and power	connection for	office copier/pr	inter					
EQUIPMENT:									

CAN\_DMS: \132040802\1

OTHER:

REMARKS: In suite with Supervisor's Office.

The Open Offices and the Operators' Day Room (aka Break Room) shall be immediately adjacent. One of the work stations in the Open Office Area shall have an operable (sliding) window into the Operators' Day Room to facilitate Dispatch of Drivers. Additionally a stainless steel cabinet with doors on either side of the wall, measuring in area approximately 0.42 metres square and 200mm deep, shall be provided for storage and charging of driver radios. Access control shall be provided on the Day Room side; locking is not required on the Open Office side. Stainless steel shelving and charging connections shall be provided for 24 radios.

### **MECHANICAL**

HVAC system: Standard office Air Supply: Standard Office, Ceiling

Min. # of air changes/hr.: - Air Exhaust: Ceiling

LAVS: - Number: - Fixture: - Water Closet: - Number: - Fixture: - Urinal: - Number: - Fixture: -

Drinking - Room Thermostat: Yes

Fountain:

Floor Drain: Drain Type:

Other:

Comments:

#### **ELECTRICAL**

Receptacles: Minimum four outlets at workstation

Switches: Low Voltage - Dimmer Yes

(Qty.):

Other:

Emergency Lighting Required: All lighting on backup power (genset)

Lighting Type: LED Lighting Level (Lux): 500

Communications:

Fire Alarm to OBC3.2.4: - P.A. System Coverage Yes

Required:

T.V. Outlet

(Qty.):

Telephone/Data Outlet (Qty.) Standard plus data and power for each cubicle

Security Requirements: Access Control

A/V Systems:

City of Ottawa			
Confederation	Line	<b>Extension</b>	<b>Project</b>

Project Agreement – Schedule 15-2 Part 5 Execution Version

Comments: -

**NOTES** 

Building	Moodie LMSF	Office Building					
Room Name:	Transportation	Quiet Room				Room Nur	nber: I
ARCHITECTUI	RAL						
Function:	Quite Room for Crew	OC Transpo	Net Area:	16	m2	Number of Occupa	ints:
Fire Rating:	NA		Barrier Free:	Yes			
ROOM CHARACT	ERISTICS						
Sound Control:	Standard	Special Ceil Conditions:	ing				
STC Rating:	45	Special Floo Conditions	or				
Other:	-	Special Wal	l Conditions :				
ROOM FINISHES							
Floor:	CPT	Base:	RB	Wall:	PT		
Ceiling:	LAT	Millwork:					
Doors (Size):	900x2100	Type:		Fire Rating:		Hardware:	
O/H Doors		Type:	-	Fire Rating:	-	Hardware:	-
(Size):		_				<b>.</b> .	
Windows:	-	Frame:	-	Fire Rating:	-	Glazing:	-
Wind Screens:	-	Frame:	-	Fire Rating:	-	Glazing:	-
Security Barriers:	•	Frame:	-	Fire Rating:	-	Glazing:	-
MILLWORK							
Counter:	-	Matl:	-	Comment:			
Shelving:	-	Matl:	-	Comment:	-		
FIXTURES:	-						
EQUIPMENT:							
OTHER:							
OTTEN.							
REMARKS:							

MECHANICAL

HVAC system: Standard office Air Supply: Standard Office, Ceiling

Min. # of air changes/hr.: - Air Exhaust: Ceiling

LAVS: - Number: - Fixture: - Water Closet: - Number: - Fixture: - Urinal: - Number: - Fixture: -

Drinking - Room Thermostat: Yes

Fountain:

Floor Drain: Drain Type: -

Other:

Comments:

**ELECTRICAL** 

Receptacles: Minimum four outlets at workstation

Switches: Low Voltage - Dimmer Yes

(Qty.):

Other: -

Emergency Lighting Required: All lighting on backup power (genset) and UPS

Lighting Type: LED Lighting Level (Lux): 200

Individually controlled task lighting to be provided at work station

Communications:

Fire Alarm to OBC3.2.4: P.A. System Coverage Yes

Required:

T.V. Outlet

(Qty.):

Telephone/Data Outlet (Qty.) Standard

Security Requirements: A/V Systems: -

Comments: -

**NOTES** 

Building	Moodie LMSF Office Building				
Room Name:	OC Transpo Server			Room Number:	NA

Function: OC Transpo Computer Equip. Net Area: 60 m2 Number of Occupants: 1

Fire Rating: 1-hr Barrier Free: Yes

**ROOM CHARACTERISTICS** 

Sound Control: Standard Special Ceiling

Conditions:

STC Rating: 55 Special Floor Antistatic raised access floor

Conditions

Other: - Special Wall Conditions

**ROOM FINISHES** 

Floor: RAF Base: RB Wall: PT/minimum 10m² comm. backboard

Ceiling: LAT Millwork:

Doors (Size): 900x2100 Type: Fire Rating: 20 Hardware: Access Control

O/H Doors Type: - Fire Rating: - Hardware: -

(Size):

Windows:Frame:-Fire Rating:-Glazing:-Wind Screens:-Frame:-Fire Rating:-Glazing:-

Security Barriers: - Frame: - Fire Rating: - Glazing: -

**MILLWORK** 

Counter: - Matl: Comment: Shelving: - Matl: Comment:

FIXTURES: -

EQUIPMENT: -

OTHER: -

REMARKS: Will serve as SER Room.

MECHANICAL

HVAC system: 3x Redundant Data Center Type Air Supply: Below floor (see comments)

Min. # of air changes/hr.: - Air Exhaust: Ceiling

LAVS: - Number: - Fixture: - Water Closet: - Number: - Fixture: - Urinal: - Number: - Fixture: -

Drinking - Room Thermostat: -

Fountain:

Floor Drain: Drain Type:

Other: Provide clean agent and pre-action fire sprinkler system.

Comments: Provide minimum 3-tons HVAC. System shall be on emergency backup power (genset). Volume shall be

controllable at each diffuser.

**ELECTRICAL** 

Receptacles: Under floor, on emergency backup power

Switches: Low Voltage - Dimmer (Qty.): (Qty.):

Other: -

Emergency Lighting Required: All lighting on backup power (genset) and UPS

Lighting Type: LED Lighting Level (Lux): 200

\_

Communications: Tie to OC Transpo [REDACTED]

Fire Alarm to OBC3.2.4: - P.A. System Coverage Yes

Required:

T.V. Outlet

(Qtv.):

Telephone/Data Outlet (Qty.)

Security Requirements: Provide access control hardware

A/V Systems:

Comments: Fire stop all conduit

**NOTES** 

RFP: Request for Quotation CAN DMS: \132040802\1

OESC: Ontario Electrical Safe Code

Number of Occupants:

Building	Moodie LMSF Office Building				
Room Name:	Storage			Room Number:	NA
ARCHITECTU	RAL				

Net Area:

Barrier Free:

**ROOM CHARACTERISTICS** 

None

Sound Control: Standard Special Ceiling

Storage area for OC Transpo Staff

Conditions:

STC Rating: 45 Special Floor:

Conditions

Other: - Special Wall Conditions Provide wall protection to 2m above finished floor, sufficient to

resist damage from carts

20

Yes

m2

**ROOM FINISHES** 

Function:

Fire Rating:

**ERC FRP** Wall: FRP to 2400mm AFF Floor: Base: **PMC** Ceiling: Millwork: Doors (Size): 1800x2100 Fire Rating: Access Type: Hardware: Control O/H Doors Type: Fire Rating: Hardware: (Size): Windows: Fire Rating: Frame: Glazing: Wind Screens: Fire Rating: Frame: Glazing: Security Barriers: Frame: Fire Rating: Glazing:

MILLWORK -

Counter: - Matl: Comment:

Shelving: Steel Matl: Comment: Minimum 54m adjustable shelving (4 tiers)

Adjustable 610mm deep; 300 kg per 1000mm load

capacity

FIXTURES: -

EQUIPMENT: Heavy duty industrial shelving, min 500 kg/m<sup>2</sup>; 600mm deep, min. 100 lm; brace at floor and floor deck above

OTHER: -

REMARKS:

MECHANICAL

HVAC system: **Typical** office

Air Supply Exhaust:

Min. # of air changes/hr.:

Number:

Air Exhaust:

LAVS:

Number: Number: Fixture:

Water Closet: Urinal:

Fixture: Fixture:

Drinking

Room Thermostat:

Fountain:

Floor Drain:

Drain Type:

Other:

Comments:

ELECTRICAL

One per each cart stall; one duplex on each wall minimum Receptacles:

Switches: Low Voltage (Qty.): Dimmer

(Qty.):

Other:

Emergency Lighting Required: Exit level only

Lighting Type: **LED**  Lighting Level (Lux): 400

Communications:

Fire Alarm to OBC3.2.4: P.A. System Coverage Yes

Required:

T.V. Outlet

(Qty.):

Telephone/Data Outlet (Qty.)

Security Requirements: **Access** 

Control

A/V Systems:

Comments:

### **NOTES**

RFP: Request for Quotation
OESC: Ontario Electrical Safe Code

Building	Moodie LMSF	Office Building					
Room Name:	Transportation Supervisors		Transportation Supervisors			Room Numb	ber: N
ARCHITECTU	<b>IRAL</b>						
Function:	Office for OC T Supervisor	ranspo Crew	Net Area:	18	m2	Number of Occupan	its: 2
Fire Rating:	NA		Barrier Free:	Yes			
ROOM CHARAC	TERISTICS						
Sound Control:	Standard	Special Cei Conditions:					
STC Rating:	45	Special Floo Conditions	or				
Other:	-		Il Conditions :				
ROOM FINISHES			20	147 11	<b>n</b> -		
Floor: Ceiling:	CPT LAT	Base: Millwork:	RB	Wall:	PT		
Doors (Size):	900x2100	Type:		Fire Rating:		Hardware:	Acces Contro
O/H Doors (Size):		Type:	-	Fire Rating:	-	Hardware:	-
Windows:	-	Frame:	-	Fire Rating:	-	Glazing:	-
Wind Screens:	-	Frame:	-	Fire Rating:	-	Glazing:	-
Security Barriers:	-	Frame:	-	Fire Rating:	-	Glazing:	-
MILLWORK		N/a-ti-		Comment:			
Counter: Shelving:		Matl: Matl:	•	Comment:	-		
FIXTURES:	-						
EQUIPMENT:							

CAN\_DMS: \132040802\1

OTHER:

**REMARKS:** 

All OC Transpo communications systems shall be accessible from this room. Provide 2 each of: desk, credenza, book shelving, and guest chair.

MECHANICAL

Standard Office, Ceiling HVAC system: Standard office Air Supply:

Min. # of air changes/hr.: Air Exhaust: Ceiling

LAVS: Number: Fixture: Water Closet: Number: Fixture: Urinal: Number: Fixture:

Drinking Room Thermostat: Yes

Fountain:

Floor Drain: Drain Type:

Other:

Comments:

**ELECTRICAL** 

Receptacles: Minimum four outlets at workstation

Switches: Low Voltage Dimmer

(Qty.): (Qty.): Other:

Emergency Lighting Required: All lighting on backup power (genset) and UPS

Lighting Type: Lighting Level (Lux): 200

Individually controlled task lighting to be provided at work station

Communications:

Via phone Fire Alarm to OBC3.2.4: P.A. System Coverage Required: system

only

T.V. Outlet Wall mounted

(Qty.):

Telephone/Data Outlet (Qty.) Standard

Security Requirements: Provide access control hardware

A/V Systems:

City of Ottawa			
Confederation	Line	<b>Extension</b>	<b>Project</b>

Project Agreement – Schedule 15-2 Part 5 Execution Version

Comments:

**NOTES** 

Building	Moodie LMSF Office Building				
Room Name:	Yard Control Centre			Room Number:	NA

Function: Yard Control and Redundant Net Area: 30 m2 Number of Occupants: 3

**Operations Control Centre** 

Fire Rating: 1-hr Barrier Free: Yes

**ROOM CHARACTERISTICS** 

Sound Control: Standard Special Ceiling

Conditions:

STC Rating: 45 Special Floor Antistatic raised access floor

Conditions

Other: - Special Wall Conditions

**ROOM FINISHES** 

Floor: VCT Base: RB Wall: PT

Ceiling: LAT Millwork:

Doors (Size): 900x2100 Type: Fire Rating: 20 Hardware: Access Control

O/H Doors Type: - Fire Rating: - Hardware: -

(Size):

Windows: Brise Soleil Frame: - Fire Rating: - Glazing: Wind Screens: - Frame: - Fire Rating: - Glazing: Security Barriers: - Frame: - Fire Rating: - Glazing: -

**MILLWORK** 

Counter: - Matl: SS Comment: Shelving: - Matl: SS Comment:

FIXTURES: YCC workstations will require space for 7 monitors all associated peripherals: 2 monitors for CBTC, 2 for

SCADA, 1 for P25 Radio touchscreen, 1 for CCTV, 1 for ProjectCo business network

**EQUIPMENT**:

OTHER: Provide minimum two YCC workstations. To the fullest extent possible, YCC Workstations shall have

panoramic view of yard in south and west directions. Provide one workstation for OC Transpo.

REMARKS: All OC Transpo communications systems shall be accessible from the OC Transpo workstation;

workstations shall have functionality of similar capacity to those at the primary OCC.

MECHANICAL

HVAC system: Typical office Air Supply:

Min. # of air changes/hr.: - Air Exhaust: Ceiling

LAVS: - Number: - Fixture: - Water Closet: - Number: - Fixture: - Urinal: - Number: - Fixture: -

Drinking - Room Thermostat: Yes

Fountain:

Floor Drain: Drain Type: -

Other:

Comments: Provide one diffuser per YCC workstation and not less than one per every 10m<sup>2</sup> or portion thereof. System

shall be on emergency backup power (genset). HVAC volume shall be controllable at each workstation

**ELECTRICAL** 

Receptacles: Minimum four outlets per workstation

Switches: Low Voltage - Dimmer One dimmer to serve room

(Qty.):

Other: -

Emergency Lighting Required: All lighting on backup power (genset) and UPS

Lighting Type: LED Lighting Level (Lux): 200 -

Individually controlled task lighting to be provided at each work station

Communications:

Fire Alarm to OBC3.2.4: - P.A. System Coverage **Yes** 

Required:

T.V. Outlet Minimum 1320mm LCD display at north wall,

(Qty.):

Telephone/Data Outlet (Qty.) Minimum four outlets per workstation and at each LCD display

Security Requirements: Provide access control hardware

A/V Systems: 3 1320mm wall mounted LCD displays to be provided which are capable of displaying

various CBTC and SCADA displays as required by YCC staff

Comments:

# **NOTES**

RFP: Request for Quotation
OESC: Ontario Electrical Safe Code

Building	Moodie LMSF Office Building				
Room Name:	Typical Multiple-Occupant Wash Room			Room Number:	NA

Function: Wash Room Net Area: 45 m2 Number of Occupants: Varies

Fire Rating: NA Barrier Free: Yes

**ROOM CHARACTERISTICS** 

Sound Control: Standard Special Ceiling

Conditions:

STC Rating: 55 Special Floor

Conditions

Other: - Special Wall Conditions :

**ROOM FINISHES** 

Floor: PCT Base: CT Wall: PT/1220mm CT Wainscot

Ceiling: LAT Millwork:

Doors (Size): 900x2100 Type: SC Fire Rating: Varies Hardware: Class/Self Closing

O/H Doors Type: - Fire Rating: - Hardware: -

(Size):

Windows: Frame: - Fire Rating: - Glazing: - Wind Screens: - Frame: - Fire Rating: - Glazing: -

Security Barriers: - Frame: - Fire Rating: - Glazing: -

**MILLWORK** 

Counter: - Matl: Comment:

Shelving: Minimum Matl: SS Comment: Above urinals, water closets, lavatories

150 x450 (mm)

FIXTURES: As required by code but not less than one urinal and one toilet per men's wash room and two toilets per

women's wash room. Washrooms shall have not less than two lavatories. Provide stainless steel shelving

above all fixtures

EQUIPMENT: -

OTHER: Shower rooms shall be provided in the main wash rooms or locker rooms serving OC Transpo transportation

crews. Floors shall be PCT, walls full height CT. Showers shall be individual occupancy with a lockable door

and may be accessed independently from wash rooms.

**REMARKS:** 

Multi-occupant OC Transpo Crew Wash Rooms shall be accessible from within the dedicated OC Transpo suite only. Dedicated and properly sized wash rooms shall be provided separately for office areas and maintenance areas to limit soiling. Finishes shall be appropriate for each.

MECHANICAL

HVAC system: - Air Supply:

Min. # of air changes/hr.: - Air Exhaust: -

LAVS: Yes Number: Min. Per Code Fixture: Water Closet: Yes Number: Min. Per Code Fixture: Urinal: Yes Number: -Min. Per Code Fixture: -

Drinking - Room Thermostat:

Fountain:

Floor Drain: 1 per every 25m² or portion thereof Drain Type: -

Other:

Comments: Shower rooms shall have 100% exhaust air

**ELECTRICAL** 

Receptacles: 1 per lavatory

Switches: Low Voltage - Dimmer -

(Qty.): (Qty.): Other:

**Emergency Lighting Required:** 

Lighting Type: LED Lighting Level (Lux): 300

Communications:

Fire Alarm to OBC3.2.4:

- P.A. System Coverage Yes

Required:

T.V. Outlet

(Qty.):

Telephone/Data Outlet (Qty.) Security Requirements: A/V Systems: -

Comments:

# **NOTES**

RFP: Request for Quotation
OESC: Ontario Electrical Safe Code