

Appendix F

Preliminary Geotechnical Considerations

**Preliminary Geotechnical Considerations
Environmental Assessment Study
Eastern Light Rail Transit Facility
Blair Station to Trim Road
Ottawa, Ontario**

Submitted to:

AECOM Canada Ltd.
1150 Morrison Drive
Ottawa, Ontario
K2H 8S9

**Preliminary Geotechnical Considerations
Environmental Assessment Study
Eastern Light Rail Transit Facility
Blair Station to Trim Road
Ottawa, Ontario**

September 10, 2015
Project: 14-275

TABLE OF CONTENTS

1.0 INTRODUCTION.....1

2.0 BLAIR ROAD INTERCHANGE (STATION 300+000 TO 301+100).....2

2.1 Project Requirements 2

2.2 Overview of Subsurface Conditions 2

2.3 Geotechnical Considerations 3

2.3.1 Excavations 3

2.3.1.1 Overburden..... 3

2.3.1.2 Bedrock 4

2.3.1.3 Groundwater Inflow during Excavation (Short-Term)..... 4

2.3.2 Underpass Structures 5

2.3.3 Roadway Cuts 6

2.4 Impacts and Mitigation Measures..... 8

3.0 BEACON HILL SOUTH (STATION 301+100 TO 302+700)9

3.1 Project Requirements 9

3.2 Overview of Subsurface Conditions10

3.3 Geotechnical Considerations10

3.3.1 Embankment Widening10

3.4 Impacts and Mitigation Measures.....11

4.0 MONTREAL ROAD INTERCHANGE (STATION 302+700 TO 303+800)12

4.1 Project Requirements12

4.2 Overview of Subsurface Conditions12

4.2.1 Previous Investigations by Others.....12

4.2.2 Preliminary Borehole Investigation.....12

4.2.2.1 Methodology12

4.2.2.2 Subsurface Conditions.....14

4.3 Geotechnical Considerations15

4.3.1 Overpass Structure15

4.3.2 Approach Embankments.....18

4.4 Impacts and Mitigation Measures.....19

5.0 GREEN'S CREEK TO TRIM ROAD (STATION 303+800 TO 312+200)20

5.1 Project Requirements20

5.2 Overview of Subsurface Conditions20

5.3 Geotechnical Considerations20

5.3.1 Regrading Existing Embankments (Sir-George-Étienne Cartier Underpass).....20

5.4 Impacts and Mitigation Measures.....21

TABLE OF CONTENTS - CONTINUED

6.0 TRIM ROAD INTERCHANGE (STATION 312+200 TO 312+900)21

6.1 Project Requirements21

6.2 Overview of Subsurface Conditions21

6.3 Geotechnical Considerations21

6.3.1 Underpass Structure21

6.3.2 Approach Embankments.....24

6.4 Impacts and Mitigation Measures.....25

7.0 ADDITIONAL CONSIDERATIONS26

7.1 Eastern LRT Stations26

7.2 Culvert Crossings.....27

7.3 Track Bed27

7.4 Vibrations.....28

7.5 Noise Wall and Lighting Foundations28

7.6 Additional Investigation and Comments28

LIST OF TABLES

Table 2.1 – Summary of Permanent Retaining Wall Options.....6

Table 2.2 – Impacts and Mitigation Measures (Blair Road Interchange).....9

Table 3.1 – Impacts and Mitigation Measures (Beacon Hill South)11

Table 4.1 – Borehole Details13

Table 4.2 – Summary of Atterberg Limit Test Results15

Table 4.3 – Summary of Deep Foundation Alternatives at Montreal Road16

Table 4.4 – Impacts and Mitigation Measures (Montreal Road Interchange)19

Table 6.1 – Summary of Deep Foundation Alternatives at Trim Road22

Table 6.2 – Impacts and Mitigation Measures (Trim Road Interchange).....25

Table 7.1 – Preliminary Design Information for the Transit Stations26

LIST OF APPENDICES

| | |
|------------|---|
| Appendix A | Proposed Eastern LRT Plan and Profile (Sheets 1 to 22) |
| Appendix B | Blair Road Interchange Relevant Borehole Logs by Others |
| Appendix C | Montreal Road Interchange Relevant Borehole Logs by Others Record of Boreholes 15-1 and 15-2 Figure C1 |

1.0 INTRODUCTION

As identified in the 2013 Transportation Master Plan (TMP), consideration is being given to extending the proposed Light Rail Transit (LRT) facility further east to Orleans. The alignment for the Eastern LRT is envisioned along the Ottawa Road 174 (OR 174) corridor between Blair Station and Trim Road. Consideration has been given to locating the Eastern LRT north of OR 174, south of OR 174, or within the median (i.e., between the eastbound/westbound lanes). An inventory of the expected soil, bedrock and groundwater conditions for the study area is provided in our draft report titled: “Geotechnical Inventory, Environmental Assessment Study, Eastern Light Rail Transit Facility, Blair Station to Trim Road, Ottawa, Ontario”, dated October 31, 2014.

Following an evaluation of the various alternatives, it is understood that the preferred location for the Eastern LRT is within the median between Green’s Creek and Trim Road. Between Green’s Creek and Blair Station, the preferred location for the Eastern LRT is north of OR 174. The proposed alignment is provided on Sheets 1 to 22 in Appendix A.

The optimal solution for the Eastern LRT will include construction of railway infrastructure, transit stations, culvert/bridge structures and grade separation of existing roadways. Relatively high embankments and deep cuts will be constructed.

This report provides an overview of the possible construction and operational impacts, including preliminary design considerations and mitigation measures, from a geotechnical point of view, based on our interpretation of the available information and project requirements. It is stressed that the information in the following sections is provided for preliminary planning and costing purposes only. It should be noted that the proposed Eastern LRT is in the same corridor as the proposed widening of OR 174; however, this report addresses the proposed Eastern LRT only as this project is expected to proceed first. Impacts and preliminary geotechnical considerations for the OR 174 widening will be provided under a separate cover.

For the purposes of this report, we have divided the proposed Eastern LRT alignment into the following five (5) segments:

- Segment 1 – Blair Road Interchange (Station 300+000 to 301+100)
- Segment 2 – Beacon Hill South (Station 301+100 to 302+700)
- Segment 3 – Montreal Road Interchange (Station 302+700 to 303+800)
- Segment 4 – Green’s Creek to Trim Road (Station 303+800 to 312+200)
- Segment 5 – Trim Road Interchange (Station 312+200 to 312+900)

An overview of the possible construction and operational impacts, including preliminary design considerations and mitigation measures, for each segment of the alignment are provided in the following sections.

2.0 BLAIR ROAD INTERCHANGE (STATION 300+000 TO 301+100)

2.1 Project Requirements

The proposed Eastern LRT alignment between Blair Station (Station 300+000) and Station 301+100 is located north of OR 174. The proposed alignment will cross below the following existing roadways/embankments (from west to east):

- Westbound on-ramp to OR 174 from southbound Blair Road;
- Blair Road;
- Westbound on-ramp to OR 174 from northbound Blair Road; and
- OR 174 off-ramp to Blair Road.

As part of the proposed plans, the existing transitway on-ramp and off-ramp will be decommissioned.

This portion of the Eastern LRT alignment is generally in cut, with the exception of the grades approaching Blair Station where the Eastern LRT will be at or slightly above existing grade. In general, the proposed grades are located about 2 to 5 metres below existing grade, increasing to between 7 and 10 metres below the surface of the current embankments.

In order to implement the Eastern LRT between Blair Station (Station 300+000) and Station 301+100, construction of new underpass structures will be required, including permanent retaining walls and, where possible, open cut sections with suitable graded side slopes.

2.2 Overview of Subsurface Conditions

As part of a previous geotechnical investigation for the east transitway extension, twelve (12) boreholes were advanced along the proposed Eastern LRT alignment. Details of the boreholes are provided in the Golder Associates Ltd. report titled: “Geotechnical Investigation, Subsurface Conditions, East Transitway, Station 12+680 to 15+150, Regional Municipality of Ottawa-Carleton”, dated January 1988.

In general, the boreholes encountered fill material over glacial till and shale bedrock. In the area of the Blair Road interchange, the overburden thickness was found to range between 2 and 5 metres, excluding the current embankment fills. Based on the results of the boreholes, the bedrock surface in the area of the Blair Road interchange is located between elevation 72 and 74 metres.

East of the Blair Road interchange (i.e., east of about Station 300+500), the overburden deposits thicken and are composed of fill material over native deposits of silty sand, silty clay, silt, and glacial till.

The bedrock encountered during the investigation consisted of laminated dark grey shale of the Billings formation. The upper portion of the bedrock is weathered and/or fractured.

Along the proposed Eastern LRT alignment, the groundwater level was found to be within about 2 metres of the ground surface (elevation 71 to 78 metres).

The approximate locations of the relevant boreholes previously advanced by Golder Associates Ltd. are shown on Sheets 1 to 3 in Appendix A. A copy of the Record of Borehole sheets for the relevant boreholes are provided in Appendix B for reference.

2.3 Geotechnical Considerations

2.3.1 Excavations

2.3.1.1 Overburden

Excavations for the structures and walls will be carried out through topsoil, fill materials, glacial till and, in some areas, the underlying dark grey shale bedrock. Comments regarding excavation of the overburden are provided below:

- For open cut excavations, allowance should be made for temporary excavation side slopes of 1 horizontal to 1 vertical, or flatter, extending from the bottom of the excavation (in accordance with Ontario Regulation 213/91 under the Occupational Health and Safety Act for Type 3 soil).
- In areas where space constraints dictate, the sides of excavation in overburden could be supported during construction using a shoring system, such as a pile and lagging shoring wall, driven interlocking steel sheet piles, secant concrete pile wall, or a concrete diaphragm wall. For all cases, lateral support to the shoring, such as tensioned rock anchors, will be required. It should be noted that the glacial till contains cobble and boulder obstructions which could affect the shoring installation. An allowance should be made to socket the soldier piles for a pile and lagging wall into the bedrock using predrilled holes.
- The shoring system should be designed to resist lateral earth pressures imposed on the shoring from the weight of the retained soil and any other surcharge loads. The lateral earth pressures acting on the shoring system will depend on the type of shoring system used and on the type of lateral support.
- The type of shoring used on this project should be based on the permissible movement behind the shoring as well as space constraints. Some unavoidable inward horizontal movement and settlement of the ground behind the retaining walls should be anticipated,

which could affect existing structures and services located behind the retaining walls. The amount of movement will depend on the type of shoring system used and will be much less for secant concrete pile and diaphragm walls (relative to pile and lagging and steel sheet pile walls).

2.3.1.2 Bedrock

Comments regarding excavation of the shale bedrock are provided below:

- Bedrock removal at this site could be carried out using drill and blasting, hoe ramming techniques in conjunction with line drilling on close centres, or a combination of both. In areas where an upper layer of fractured bedrock is encountered, rock removal could likely be carried out using hydraulic excavation equipment. Any blasting should be carried out in a manner that maintains vibration levels below the threshold values established for the project.
- The shoring should be setback from the edge of the adjacent bedrock excavation. The setback requirements will depend on the type of shoring, socket depth, and depth of bedrock excavation.
- Provided that good bedrock excavation techniques are used, the bedrock could be excavated using near vertical side walls.
- The bedrock contains near vertical joints and bedding planes and, therefore, some vertical and horizontal over break of the bedrock should be expected (i.e., the bedrock will likely break at a horizontal bedding plane below the planned excavation depth).
- The shale bedrock at this site has the potential to swell due to the oxidation of pyrite and the subsequent formation of jarosite and gypsum between the shale laminations. The shale bedrock below any proposed structures should be covered immediately following exposure with a protection layer of sulphate resistant concrete (50 to 75 millimetre thick). Any vertical surfaces should be protected using shotcrete.

2.3.1.3 Groundwater Inflow during Excavation (Short-Term)

Based on the results of the previous boreholes advanced in the area of the Blair Road interchange, excavation in overburden and bedrock below the groundwater level will likely be required. Comments regarding groundwater inflow into the excavations are provided below:

- Based on our previous experience, no unusual constraints are anticipated during excavation of the glacial till and shale bedrock below the groundwater level.
- Groundwater inflow should be relatively small and controlled by pumping from filtered sumps within the excavation.

- It is not expected that short term pumping during construction will have a significant effect on nearby structures and services.
- Allowance should be made for a Permit to Take Water (PTTW) in accordance with Ministry of the Environment and Climate Change (MOECC) requirements.

2.3.2 Underpass Structures

As previously indicated, construction of new underpass structures will be required in order to implement the Eastern LRT. Preliminary considerations for design of the underpasses are provided below:

- Based on the results of the previous boreholes advanced in the area of the Blair Road interchange, new underpass structures will likely be founded on spread footing foundations bearing directly on competent shale bedrock.
- Spread footing foundations bearing on or within competent shale bedrock could be sized using a factored bearing resistance at Ultimate Limit States (ULS) of between about 1,500 to 3,000 kilopascals. These bearing pressures assume that all soil and fractured/weathered bedrock is removed from the bearing surfaces, and that no significant soil filled seams exist in close proximity to the bearing surface. In accordance with the Canadian Highway Bridge Design Code (CHBDC), the geotechnical resistance at ULS was factored using a resistance factor of 0.5. The geotechnical reaction at SLS will be greater than the factored geotechnical resistance at ULS; as such, ULS conditions will govern.
- Based on available information, seismic Site Class C could be used for preliminary design purposes. Shear wave velocity testing could be carried out to evaluate whether a more favourable Site Class (i.e., A or B) can be specified.
- Shear resistance of the footings against lateral sliding could be calculated using an unfactored angle of friction of 25 degrees between the shale bedrock and the underside of the foundations. In accordance with the CHBDC, the geotechnical resistance to sliding should be factored using a resistance factor of 0.8.
- The depth of the spread footings should be at least 1.8 metres below finished grade to provide adequate frost protection of the footings. Alternatively, the required frost protection could be provided by means of a combination of earth cover and extruded polystyrene insulation.
- The abutments should be backfilled with imported, free-draining, non-frost susceptible granular material meeting Granular B Type I or II requirements. The abutment and wing walls should be design to resist the static and seismic lateral thrusts imposed on the structures as a result of earth pressures.

2.3.3 Roadway Cuts

As previously indicated, the proposed grades for the Eastern LRT in the area of the Blair Interchange are located about 2 to 5 metres below existing grade, increasing to between 7 and 10 metres below the surface of the current embankments. It is noted that the proposed grades for the Eastern LRT are below the reported groundwater levels.

The following alternatives could be considered for treating the sides of the roadway cuts:

- Alternative 1 - Open cut with permanent excavation side slopes of about 2.5 horizontal to 1 vertical, or flatter, within overburden. In bedrock, near vertical side walls would likely be suitable, assuming a suitable setback between the toe of the overburden slope and the bedrock face. A swale would be required at the toe of the rock slope since there will be some unavoidable degradation of the bedrock with time, and subsequent rock falls.
- Alternative 2 - Provide permanent retaining walls, such as a cast in place concrete wall, Mechanically Stabilized Earth (MSE) wall, pile and lagging shoring wall, secant concrete pile wall, or a concrete diaphragm wall.

Comments on various types of permanent retaining walls are summarized in Table 2.1.

Table 2.1 – Summary of Permanent Retaining Wall Options

| Support Option | Comments |
|--|---|
| Option 2A: Cast in Place Concrete Wall | <ul style="list-style-type: none">• To allow for construction, excavation side slopes of 1 horizontal to 1 vertical, or flatter, are required. Alternatively, temporary shoring could be considered (e.g., socketed pile and lagging wall). |
| | <ul style="list-style-type: none">• To prevent buildup of hydrostatic pressure behind the retaining wall, the backfill material should be drained with a perforated drain at the base of the wall. |
| | <ul style="list-style-type: none">• In areas where bedrock cuts are required, the walls should be constructed at least 1.8 metres below finished grade for frost protection purposes. |
| | <ul style="list-style-type: none">• Minor groundwater seepage from the overburden and bedrock should be anticipated. Long-term groundwater handling/disposal will be required. |

Table 2.1 – Summary of Permanent Retaining Walls Options (Continued)

| Support Option | Comments |
|-------------------------|---|
| Option 2B: MSE Walls | <ul style="list-style-type: none">• The excavation should be suitably sized to allow for placement of the reinforcement behind the wall. As a general guide, the reinforcement typically extends a horizontal distance equal to about 80% of the ultimate height of the wall.• To allow for construction, excavation side slopes of 1 horizontal to 1 vertical, or flatter, are required. Alternatively, temporary shoring could be considered (e.g., socketed pile and lagging wall).• To prevent buildup of hydrostatic pressure behind the MSE wall, the backfill material should be drained with a perforated drain at the base of the wall.• In areas where bedrock cuts are required, the walls could be constructed on the bedrock surface. For this case, the walls should be suitably set back from the edge of the bedrock excavation (the setback requirements will depend on the stability and frost susceptibility of the bedrock). In bedrock, near vertical side walls would likely be suitable assuming that a catch bench is provided at the bottom of the rock slope. Due to the presence of swelling shale, protection of the bedrock face will be required (e.g., shotcrete).• Minor groundwater seepage from the overburden and bedrock should be anticipated. Long-term groundwater handling/disposal will be required. |
| | <ul style="list-style-type: none">• The overburden and bedrock could be permanently supported using a pile and lagging wall (with or without a facing applied).• The soldier piles should be socketed into the underlying bedrock below the depth of excavation using predrilled holes.• Lateral support to the shoring, such as tensioned rock anchors, will be required.• The overburden contains cobble and boulder obstructions which could affect the shoring installation.• Some unavoidable inward horizontal movement and settlement of the ground behind the retaining walls should be anticipated, which could affect existing structures and services located behind the retaining walls.• Minor groundwater seepage from the overburden and bedrock should be anticipated. Long-term groundwater handling/disposal will be required. |

Table 2.1 – Summary of Permanent Retaining Walls Options (Continued)

| Support Option | Comments |
|---|---|
| Option 2D: Secant Concrete Pile Wall or Concrete Diaphragm Wall | <ul style="list-style-type: none">• The sides of the excavation could be supported permanently using rigid secant concrete pile walls or concrete diaphragm walls (with a facing applied) socketed into the underlying bedrock below the level of the Eastern LRT.• Depending on the height of the wall, some form of lateral support to the shoring, such as tensioned rock anchors, may be required.• Although the most costly of the options discussed, the main advantages of using rigid secant concrete pile walls or concrete diaphragm walls are:<ul style="list-style-type: none">○ Ground movement behind the walls will be much less, relative to pile and lagging and steel sheet pile walls.○ Secant concrete pile walls or concrete diaphragm walls have a relatively low permeability and, as such, groundwater inflow from the overburden and bedrock will be much less, relative to Options 2A to 2C. In other words, secant concrete pile walls or concrete diaphragm walls would essentially “cut-off” horizontal groundwater inflow from the overburden and bedrock. Some minor groundwater seepage from the base of the excavation, and surface water that infiltrates into the LRT ballast material, will require long-term handling and disposal. |
| | |

2.4 Impacts and Mitigation Measures

A summary of the possible construction and operational impacts in the area of the Blair Road interchange are summarized in Table 2.2.

Table 2.2 – Impacts and Mitigation Measures (Blair Road Interchange)

| Type | Impact(s) | Mitigation Measure(s) |
|------------------------|---|---|
| Operational Impact(s) | <ul style="list-style-type: none">The handling and disposal of groundwater, and surface water, entering the cut sections of the Eastern LRT could present some constraints.Long-term seepage will result in permanent groundwater lowering in the vicinity of the alignment. Excessive groundwater level lowering within the bedrock may result in swelling/heaving of unprotected shale bedrock due to drying and exposure to oxygen. Basement floor slabs may be susceptible to heaving if founded on unprotected (i.e., without adequate soil cover or a concrete protection layer) shale bedrock within the zone of influence of groundwater drawdown. | <ul style="list-style-type: none">Construction of rigid secant concrete pile walls or concrete diaphragm walls (i.e., “cut-off” walls) along cut sections of the Eastern LRT. |
| Construction Impact(s) | <ul style="list-style-type: none">No significant construction impacts are anticipated. | <ul style="list-style-type: none">No significant construction impacts are anticipated. |

3.0 BEACON HILL SOUTH (STATION 301+100 TO 302+700)

3.1 Project Requirements

The proposed Eastern LRT alignment between Stations 301+100 and 302+700 is located north of OR 174. At about Station 302+125, the Eastern LRT alignment crosses the Jasmine Park Ravine.

In general, the proposed grades along this portion of the Eastern LRT will be about 1 to 2 metres above existing grade. In some areas, the proposed grades match the existing grades. At the Jasmine Park Ravine crossing, the proposed grades are about 5 metres above existing grade.

In order to implement the Eastern LRT between Stations 301+100 and 302+700, widening of the existing OR 174 embankment will be required, including extension of the existing culvert structure at the Jasmine Park Ravine.

3.2 Overview of Subsurface Conditions

Based on the available subsurface information, the subsurface conditions between Stations 301+100 and 302+700 are expected to consist primarily of deposits of silty clay, increasing in thickness from about 5 to 100 metres from west to east. Bedrock is mapped as interbedded limestone and shale (Lindsay formation), limestone (Bobcaygeon formation), and interbedded limestone and dolostone (Gull River formation).

3.3 Geotechnical Considerations

3.3.1 Embankment Widening

Along this portion of the Eastern LRT (Station 301+100 to 302+700), widening of the existing OR 174 embankment is required. Preliminary considerations for embankment widening are provided below:

- All topsoil, organic material, and unsuitable fill material should be removed from the base of the embankment, and all topsoil and organic material should be removed from the existing embankment slope.
- The embankment fill material could consist of compacted material meeting OPSS Granular B Type I or II, or OPSS Select Subgrade Material.
- Final fill slopes constructed with OPSS Granular B Type I or Select Subgrade Material could be sloped at 2.5 horizontal to 1 vertical, or flatter; for Granular B Type II, fill slopes of 2.0 horizontal to 1 vertical, or flatter would be suitable. If steeper embankment slopes are required due to space limitations, a geogrid reinforced slope or a mechanically stabilized earth retaining wall could be considered.
- To avoid abrupt differential heaving at the joint between the new and existing embankment, the embankment fill material used within the zone of frost penetration below the embankment widening should be frost compatible with the fill materials below the existing OR 174 embankment; alternatively, a gradual frost heave transition should be provided.
- The proposed Eastern LRT alignment between Stations 301+100 and 302+700 is underlain by deposits of sensitive silty clay which have a reduced capacity to support loads imposed by grade raise fill material. Based on the settlement history of previous embankments constructed on sensitive silty clay deposits in the Ottawa area, the following long-term settlements (i.e., after about 10 to 20 years) are estimated for the proposed embankments within this portion of the Eastern LRT:
 - Less than 50 millimetres of settlement for embankments less than 2 metre high.
 - 100 to 150 millimetres of settlement for 5 metre high embankments (i.e., at the Jasmine Park Ravine crossing).
- The settlement below the widened portions of the embankments will likely be greater than the settlement of the existing embankment. Differential settlement could be

- problematic for buried structures (i.e., culverts) located along the base of the embankment.
- The overall stability of the embankment side slopes will depend on the ultimate height of the approach embankments and inclination of the side slopes. However, to assess the feasibility of embankment construction in this area, preliminary slope stability analyses were carried out. The results of the stability analyses indicate that a 5 metre high embankment, with side slopes constructed at 2 to 2.5 horizontal to 1 vertical, would have an adequate factor of safety against a deep seated shear failure through the silty clay. Furthermore, the preliminary slope stability analyses also indicate that a 5 metre high retaining structure would be feasible.

3.4 Impacts and Mitigation Measures

A summary of the possible construction and operational impacts between Blair Station (Station 300+000) and Station 301+100 are summarized in Table 3.1.

Table 3.1 – Impacts and Mitigation Measures (Beacon Hill South)

| Type | Impact(s) | Mitigation Measure(s) |
|------------------------|--|--|
| Operational Impact(s) | <ul style="list-style-type: none">• Differential settlement of any buried structures (i.e., culverts) located along the base of new and existing embankment (e.g., at the Jasmine Park Ravine crossing). Differential settlement may negatively impact the long-term performance of the structure.• Long-term settlement along the length of the newly constructed embankment may also result in long-settlement of Eastern LRT infrastructure supported on the embankment. | <ul style="list-style-type: none">• Track re-ballasting could be a viable alternative to address the long-term settlements.• If the estimated settlements cannot be tolerated, the use of lightweight fill material (e.g., expanded polystyrene, Isofill, slag fill, etc.) as part of the embankment construction could be considered in order to limit the stress increase on the underlying silty clay and reduce post-construction settlement. The estimated settlement of the embankments will be refined during detailed design. |
| Construction Impact(s) | <ul style="list-style-type: none">• Removal and replacement of any topsoil, organic material, and unsuitable fill material encountered below the base of the embankment. | <ul style="list-style-type: none">• Evaluation of topsoil, organic material, and unsuitable fill material thicknesses during detailed design.• If the thickness of any unsuitable material is excessive, some form of temporary shoring may be required in order to allow for its removal. |

4.0 MONTREAL ROAD INTERCHANGE (STATION 302+700 TO 303+800)

4.1 Project Requirements

At the Montreal Road interchange, the proposed location of the Eastern LRT transitions from north of OR 174 to within the median of OR 174 (east of about Station 303+250). The proposed alignment will cross over the following roadways (from west to east):

- Realigned Westbound on-ramp to OR 174 from southbound Montreal Road;
- Montreal Road;
- Westbound on-ramp to OR 174 from northbound Montreal Road; and
- Westbound OR 174.

As part of the proposed plans, the existing transitway on-ramp and off-ramp will be decommissioned.

The profile for the Eastern LRT at the Montreal Road interchange is well above existing grades (up to about 12 metres at Montreal Road). In order to implement the Eastern LRT, an overpass structure will be required (spanning a distance of 700 to 900 metres), along with approach embankments and permanent retaining walls.

4.2 Overview of Subsurface Conditions

4.2.1 Previous Investigations by Others

As part of the geotechnical investigation carried out in 1956 by G.C. McRostie Consulting Civil Engineers for the Montreal Road interchange, two (2) boreholes were advanced in the area of the Eastern LRT at Montreal Road. In addition, the Ministry of Transportation (MTO) advanced one (1) borehole just west of Green’s Creek as part of a feasibility study for Highway 17 in 1978.

In general, the boreholes encountered about 32 to 33 metres of silty clay underlain by about 6 to 7 metres of glacial till over shale bedrock. The total overburden thickness was found to be about 39 metres.

The approximate locations of the relevant boreholes previously advanced by G.C. McRostie Consulting Civil Engineers and the MTO are shown on Sheets 6 and 7 in Appendix A. A copy of the Record of Borehole sheets for the relevant boreholes are provided in Appendix C for reference.

4.2.2 Preliminary Borehole Investigation

4.2.2.1 Methodology

In order to supplement the existing geotechnical information, two (2) boreholes, numbered 15-1 and 15-2, were advanced in the area of the Montreal Road interchange and Green’s Creek

crossing, respectively (i.e., in areas where major infrastructure improvements are anticipated). The boreholes were advanced using a truck mounted drill rig supplied and operated by George Downing Estate Drilling of Grenville-sur-la-Rouge, Quebec. Details for the boreholes are provided in Table 4.1.

Table 4.1 – Borehole Details

| Borehole | Location | Program of Investigation |
|----------|---------------------------|--|
| 15-1 | Montreal Road Interchange | <ul style="list-style-type: none">Borehole 15-1 was advanced through the shoulder of the westbound Transitway On-Ramp to OR 174 at Montreal Road to about 30.5 metres below ground surface. Dynamic cone penetration testing was carried out in borehole 15-1 between 16.8 and 30.5 metres below ground surface. |
| 15-2 | Green's Creek Crossing | <ul style="list-style-type: none">Borehole 15-2 was advanced through the shoulder of the westbound OR 174 to about 30.5 metres below ground surface. Dynamic cone penetration testing was carried out in borehole 15-2 between 16.8 and 30.5 metres below ground surface. |

Standard penetration tests were carried out in the boreholes and samples of the soils encountered were recovered using a 50 millimetre diameter split barrel sampler. In situ vane shear testing was carried out in the boreholes to measure the undrained shear strength of the silty clay deposits.

The field work was supervised throughout by a member of our engineering staff, who located the boreholes, logged the samples and observed the in-situ testing. Following the field work, the soil samples were returned to our laboratory for examination by a geotechnical engineer. Selected samples of the soil were tested for water content and Atterberg limits.

The borehole locations were selected by Houle Chevrier Engineering Ltd. personnel and positioned at the site relative to existing site features. The ground surface elevations and locations of the boreholes were determined using a Trimble R8 GPS survey instrument. The elevations are referenced to Geodetic datum.

The approximate locations of the boreholes are shown on Sheets 6 and 7 in Appendix A. Descriptions of the subsurface conditions logged in the boreholes are provided on the Record of Borehole sheets in Appendix C.

4.2.2.2 Subsurface Conditions

Granular Shoulder Material

Boreholes 15-1 was advanced through the shoulder of the westbound Transitway On-Ramp to OR 174 at Montreal Road and encountered about 2.1 metres of grey, crushed sand and gravel (base/subbase material). Borehole 15-2 was advanced through the shoulder of the westbound OR 174 and encountered about 1 metre of grey, crushed sand and gravel (base/subbase material). The water content of the base/subbase material is about 2 to 4 percent.

Silty Clay

Native deposits of silty clay were encountered in boreholes 15-1 and 15-2 beneath the base/subbase material at 2.1 and 1.0 metres below ground surface, respectively. The boreholes were terminated within inferred silty clay deposits at 30.5 metres below ground surface.

The upper part of the silty clay is weathered grey brown. Standard penetration tests carried out in the weathered, grey brown silty clay gave N values varying from 2 to 7 blows per 0.3 metres of penetration. Field vane shear strength tests carried within the weathered silty clay in boreholes 15-1 and 15-2 gave shear strengths of 69 to 96 kilopascals, which indicates a stiff consistency. At borehole 15-1, the weathered, grey brown silty clay has a thickness of about 2.5 metres and extends to a depth of about 4.6 metres below ground surface (elevation 55.6 metres). At borehole 15-2, the weathered, grey brown silty clay has a thickness of about 2.0 metres and extends to a depth of about 3.1 metres below ground surface (elevation 47.4 metres). The water content of the weathered silty clay varies from 28 to 61 percent.

Below the weathered zone at boreholes 15-1 and 15-2, the silty clay is grey in colour. Standard penetration tests carried out in the grey silty clay gave N values varying from 1 to 4 blows per 0.3 metres of penetration. Field vane shear strength tests carried within the grey silty clay in boreholes 15-1 and 15-2 gave shear strengths of 67 to 96 kilopascals, which indicates a stiff consistency. The water content of the grey silty clay varies from 60 to 76 percent.

Dynamic cone penetration tests were carried out in boreholes 15-1 and 15-2 between about 16.8 and 30.5 metres below ground surface. At borehole 15-1, the blow counts generally increased from 4 to 36 blows per 0.3 metres of penetration. At borehole 15-2, the blow counts generally increased from 9 to 57 blows per 0.3 metres of penetration. It should be noted that the results of the dynamic cone penetration testing carried out in boreholes 15-1 and 15-2 may have been influenced by friction acting along the length of rods. The dynamic cone penetration tests were terminated at 30.5 metres below ground surface, likely within the silty clay deposits.

The results of an Atterberg limit tests carried out on samples of the silty clay are provided on Figure C1 in Appendix C. The results are summarized in Table 4.2.

Table 4.2 – Summary of Atterberg Limit Test Results

| Borehole | Water Content (%) | Liquid Limit (%) | Plastic Limit (%) | Plasticity Index | Figure |
|------------------------|-------------------|------------------|-------------------|------------------|--------|
| 15-1 (Sample No. 9) | 76 | 53 | 27 | 26 | C1 |
| 15-2 (Sample No. 5) | 69 | 56 | 27 | 29 | C1 |

This testing indicates that the silty clay has high plasticity. The water content of the sample tested is above the measured liquid limit values.

Groundwater Levels

Piezometers were not installed as part of this preliminary borehole investigation. However, based on our observations during drilling, the groundwater level is likely at 1.5 to 3.0 metres below ground surface.

4.3 Geotechnical Considerations

4.3.1 Overpass Structure

As previously indicated, construction of an overpass structure will be required in order to implement the Eastern LRT at the Montreal Road interchange. In this area, the Eastern LRT alignment is underlain by thick deposits of sensitive silty clay and deep foundations will be required (i.e., it will not be possible to achieve the required capacities from conventional spread footings founded within overburden). It is noted that the bedrock surface is located about 39 metres below ground surface. The following deep foundation alternatives could be considered:

Alternative 1 - Driven end bearing piles on sound bedrock

Alternative 2 - Socketed piles or caissons into sound bedrock

Comments on the deep foundation alternatives are summarized in Table 4.3.

Table 4.3 – Summary of Deep Foundation Alternatives at Montreal Road

| Foundation Alternative | Comments |
|---|---|
| Alternative 1: Driven end bearing piles on sound bedrock | <ul style="list-style-type: none"> The proposed structure could be supported on steel piles driven to refusal on the underlying bedrock. Buoyancy (uplift) issues are anticipated if large diameter closed ended driven steel pipe piles are used. Therefore, consideration should be given to using steel H piles. The tips of H-piles should be reinforced with steel plates to reduce the potential for damage. Cobbles and boulders should be anticipated in the glacial till. Some of the piles may be bent, driven off plumbness or location tolerance, may break, or may terminate on cobbles/boulders in the glacial till. Any defective piles should be replaced, as required. Pile capacities at this site will depend on pile type, pile dimensions, pile material and the end bearing material. As an example, the following preliminary pile capacities could be used for H piles driven to refusal within sound bedrock: <ul style="list-style-type: none"> The factored geotechnical reaction at Serviceability Limit States (SLS) could be taken as 850 kilonewtons. In accordance with the CHBDC, the geotechnical reaction at SLS was factored using a resistance factor of 0.8. The factored geotechnical resistance at ULS could be taken as 1,200 kilonewtons. In accordance with the CHBDC, the geotechnical resistance at ULS was factored using a resistance factor of 0.4. Post-construction settlement of the silty clay deposits is likely. For this case, the resulting downward movement of the soil around the piles will induce downdrag forces on the piles through negative skin friction. The downdrag load will depend on pile type, pile dimensions, and pile material and should be considered during design. Re-striking all of the piles should be carried out in order to confirm the permanence of the pile set. It should be noted that achieving permanence of the pile set on or within the shale bedrock could be problematic and several rounds of re-striking may be required in order to achieve pile load capacities. Pile caps should be provided with at least 1.8 metres of earth cover for frost protection purposes. For uplift resistance (i.e., resistance to overturning), the tensile capacity of the driven piles should be ignored. Therefore, some form of uplift resistance will be required (e.g., tensioned rock anchors). |
| | |

Table 4.3 – Summary of Deep Foundation Alternatives at Montreal Road (Continued)

| Foundation Alternative | Comments |
|---|---|
| Alternative 2: Socketed piles or caissons into sound bedrock | <ul style="list-style-type: none">Consideration could be given to founding the proposed structure on steel piles socketed and then grouted into bedrock (e.g., using the ODEX drilling system). Alternatively, large diameter concrete caissons socketed into bedrock could be considered. |
| | <ul style="list-style-type: none">For preliminary design and costing purposes, the geotechnical resistance at ULS of socketed piles or caissons that derive support only in shear within the bedrock could be calculated using an unfactored average shear resistance along the socket of about 1,000 kilopascals. The geotechnical reaction at SLS will be greater than the factored geotechnical resistance at ULS; as such, ULS conditions will govern. For socketed piles, the structural capacity of the pile will govern if it is less than the capacity derived from socket shear. |
| | <ul style="list-style-type: none">The capacity derived from socket shear could be used to provide both compression and uplift (tension) resistance. In accordance with the CHBDC, the geotechnical resistance at ULS should be factored using resistance factors of 0.4 and 0.3 for compression and tension, respectively. |
| | <ul style="list-style-type: none">Socketed micropiles or caissons that derive support in shear within the bedrock should have a nominal socket length to diameter ratio of at least 2 to 3. |
| | <ul style="list-style-type: none">Post-construction settlement of the silty clay deposits is likely. For this case, the resulting downward movement of the soil around the piles/caissons will induce downdrag forces on the piles/caissons through negative skin friction. The downdrag load will depend on pile/caisson type, pile/caisson dimensions, and pile/caisson material and should be considered during design. |
| | <ul style="list-style-type: none">Cobbles and boulders should be anticipated in the glacial till. As such, allowance should be made to break boulders, where necessary, within a temporary steel casing using churn drilling techniques or to remove any boulders encountered by the caissons. Any voids created during removal of boulders should be filled with concrete. |
| | <ul style="list-style-type: none">Pile caps (and caisson caps, if required) should be provided with at least 1.8 metres of earth cover for frost protection purposes. |

For comparison purposes, it is noted that socketed piles/caissons (Alternative 2) can provide uplift resistance whereas with driven piles, some form of uplift resistance will be required (e.g., tensioned rock anchors). Furthermore, cobbles and boulders obstructions within the glacial till are less problematic for Alternative 2 relative to Alternative 1. Higher capacities could be achieved using socketed concrete caissons relative to driven/socketed piles.

Based on the results of shear wave velocity testing that we have carried out in similar deposits in the Ottawa area, seismic Site Class E could be used for preliminary foundation design purposes. Site specific shear wave velocity testing should be carried out during the design stage to confirm the seismic Site Classification and evaluate whether a more favourable Site Class (i.e., Site Class D) can be specified. There is no potential for liquefaction of the overburden material at this site.

4.3.2 Approach Embankments

Approach embankments to the proposed overpass structure will be required. The west approach embankment will be located north of OR 174. The east approach embankment will be located within the median of OR 174. Although the height of the approach embankments are not presently known, preliminary considerations for embankment construction are provided below:

- All topsoil, organic material, and unsuitable fill material should be removed from the base of the embankments.
- The embankment fill material could consist of compacted material meeting OPSS Granular B Type I or II or OPSS Select Subgrade Material.
- Final fill slopes constructed with OPSS Granular B Type I or Select Subgrade Material could be sloped at 2.5 horizontal to 1 vertical, or flatter; for Granular B Type II, fill slopes of 2.0 horizontal to 1 vertical, or flatter would be suitable. Where steeper embankment slopes are required due to space limitations (e.g., for the east approach), some form of retaining structure, such as a geogrid reinforced slope, a cast in place concrete wall, or a Mechanically Stabilized Earth (MSE) wall could be considered. The cast in place walls could be a cantilever wall with the base extending below the ELRT, and below the zone of seasonal frost penetration. MSE walls could bear on a narrow strip footing below the zone of seasonal frost penetration.
- The approach embankments will be underlain by deposits of sensitive silty clay which have a reduced capacity to support loads imposed by grade raise fill material. Based on the settlement history of previous embankments constructed on sensitive silty clay deposits in the Ottawa area, the long-term settlement of embankments that are 4 to 5 metres high could be in the order of 100 to 200 millimetres. For embankments greater than 4 to 5 metres in height, long-term settlements in excess of 100 to 200 millimetres should be expected.
- The settlement of the embankments would be entirely differential to the rigidly supported overpass structure. Furthermore, the design of the embankments must also consider the location of OR 174 and the impact that the settlements may have on that roadway.
- The overall stability of the embankment side slopes will depend on the ultimate height of the approach embankments and inclination of the side slopes. However, to assess the feasibility of embankment construction in this area, preliminary slope stability analyses

were carried out. The results of the stability analyses indicate that 6 metre high approach embankments, with side slopes constructed at 2.5 horizontal to 1 vertical, would have an adequate factor of safety against a deep seated shear failure through the silty clay. Furthermore, the preliminary slope stability analyses also indicate that a 4 metre high vertical retaining structure would be feasible.

4.4 Impacts and Mitigation Measures

A summary of the possible construction and operational impacts in the area of the Montreal Road interchange are summarized in Table 4.4.

Table 4.4 – Impacts and Mitigation Measures (Montreal Road Interchange)

| Type | Impact(s) | Mitigation Measure(s) |
|------------------------|---|--|
| Operational Impact(s) | <ul style="list-style-type: none">Differential settlement of the approach embankments will be entirely differential to the rigidly supported overpass structure.Depending on the location of OR 174 relative to the proposed embankments, construction of the approach embankments may result in localized post-construction settlement of OR 174. | <ul style="list-style-type: none">Construction of approach slabs at the transition between the structure and embankments.Track re-ballasting could be a viable alternative to address the long-term settlementsIf the estimated settlements cannot be tolerated, the use of lightweight fill material (e.g., expanded polystyrene, Isofill, slag fill, etc.) as part of the embankment construction could be considered in order to limit the stress increase on the underlying silty clay and reduce post-construction settlement. Site pre-loading (with or without wick drains) could also be considered to reduce post-construction settlements; however, pre-loading would not mitigate the potential for settlement related impacts to OR 174. The estimated settlement of the embankments will be refined during detailed design. |
| Construction Impact(s) | <ul style="list-style-type: none">Deep foundations, which derive their capacity from the underlying bedrock, are required for support of the proposed overpass structure. The bedrock surface is reported to be located about 39 metres below ground surface. | <ul style="list-style-type: none">Various foundation alternatives are available. |

5.0 GREEN’S CREEK TO TRIM ROAD (STATION 303+800 TO 312+200)

5.1 Project Requirements

The proposed Eastern LRT alignment between Green’s Creek and Trim Road is located within the median of OR 174. In general, the proposed grades along this portion of the Eastern LRT will match the existing grades.

In order to implement the Eastern LRT between Green’s Creek and Trim Road, regrading of the toe of the existing approach embankments for the Sir-George-Étienne Cartier underpass is required. This will likely require the construction of some form of retaining structure along the toe of the embankment to allow for widening of the corridor below the existing structure.

It is noted that replacement of the Champlain Street underpass will likely be required in order to accommodate the proposed widening of OR 174. As previously indicated, the impacts and geotechnical considerations for the proposed widening of OR 174 are beyond the scope of this report.

5.2 Overview of Subsurface Conditions

Based on the available subsurface information, the subsurface conditions between Green’s Creek and Trim Road are expected to consist primarily of deposits of silty clay. Shallow bedrock is mapped near the Place D’Orléans Shopping Centre (bedrock outcrops exist at the Champlain Street overpass and the pedestrian bridge at Place D’Orléans Station). Deposits of glacial till should be expected at the transition areas between shallow bedrock and deposits of silty clay. The overburden thickness is highly variable, ranging from about 3 to 100 metres, being thinnest near areas where shallow bedrock is mapped (i.e., Place D’Orléans Shopping Centre). Bedrock is mapped as dolostone (Oxford formation), limestone (Bobcaygeon formation), and interbedded limestone and dolostone (Gull River formation).

5.3 Geotechnical Considerations

5.3.1 Regrading Existing Embankments (Sir-George-Étienne Cartier Underpass)

As previously indicated, regrading of the toe of the existing approach embankments for the Sir-George-Étienne Cartier underpass is required. This will likely require the construction of some form of retaining structure along the toe of the embankment to allow for widening of the corridor below the existing underpass. The retaining structure could consist of a geogrid reinforced slope, a cast in place concrete wall, or a Mechanically Stabilized Earth (MSE) wall. To allow for construction, excavation side slopes of 1 horizontal to 1 vertical, or flatter, are required.

The overall stability of the regraded embankment side slopes will depend on the ultimate height of the retaining structure (i.e., the amount of “trimming required at the toe of the existing embankment side slope). However, to assess the feasibility of embankment regrading in this area, preliminary slope stability analyses were carried out. The results of the stability analyses

indicate that 3 metre high retaining structure constructed along the base of an 8 metre high embankment, with side slopes of 2 to horizontal to 1 vertical, would have an adequate factor of safety against a deep seated shear failure through the silty clay.

5.4 Impacts and Mitigation Measures

No significant construction or operational impacts are anticipated along this portion of the Eastern LRT.

6.0 TRIM ROAD INTERCHANGE (STATION 312+200 TO 312+900)

6.1 Project Requirements

The proposed Eastern LRT alignment in the area of the Trim Road interchange is located within the median of OR 174. In general, the proposed grades along this portion of the Eastern LRT will match the existing grades.

In order to implement the Eastern LRT in the area of the Trim Road interchange, construction of a new overpass structure, and approach embankments, will be required to carry Trim Road over the Eastern LRT and OR 174. In addition, on and off ramps to OR 174 from Trim Road will be constructed; however, the geotechnical impacts and design considerations for the proposed ramps are beyond the scope of this report.

6.2 Overview of Subsurface Conditions

Based on our experience in the area, the area of the Trim Road interchange is underlain by thick deposits of firm to stiff, sensitive silty clay. The overburden thickness in this area is presently unknown. Drift thickness maps indicate that the bedrock surface is located between 15 and 25 metres below ground surface; however, based on our experience in the area, it is anticipated that the bedrock surface is located more than 30 metres below ground surface. Furthermore, based on our review of MOECC water well records, the bedrock surface could be located between about 60 and 80 metres below ground surface. Bedrock is mapped as interbedded limestone and dolostone (Gull River formation).

6.3 Geotechnical Considerations

6.3.1 Underpass Structure

As previously indicated, construction of an underpass structure will be required in order to implement the Eastern LRT at the Trim Road interchange. In this area, the Eastern LRT alignment is underlain by thick deposits of sensitive silty clay and deep foundations will be required (i.e., it will not be possible to achieve the required capacities from conventional spread footings founded within overburden). It is noted that the bedrock surface in this area is presently unknown, but could be located up to between 60 and 80 metres below ground surface. The following deep foundation alternatives could be considered:

Alternative 1 - Driven end bearing piles on sound bedrock

Alternative 2 - Socketed piles or caissons into sound bedrock

Comments on the deep foundation alternatives are summarized in Table 6.1.

Table 6.1 – Summary of Deep Foundation Alternatives at Trim Road

| Foundation Alternative | Comments |
|---|---|
| Alternative 1: Driven end bearing piles on sound bedrock | <ul style="list-style-type: none">The proposed structure could be supported on steel piles driven to refusal on the underlying bedrock.Buoyancy (uplift) issues are anticipated if large diameter closed ended driven steel pipe piles are used. Therefore, consideration should be given to using steel H piles. The tips of H-piles should be reinforced with steel plates to reduce the potential for damage.Pile capacities at this site will depend on pile type, pile dimensions, pile material and the end bearing material. As an example, the following preliminary pile capacities could be used for H piles driven to refusal within sound bedrock:<ul style="list-style-type: none">The factored geotechnical reaction at Serviceability Limit States (SLS) could be taken as 850 kilonewtons. In accordance with the CHBDC, the geotechnical reaction at SLS was factored using a resistance factor of 0.8.The factored geotechnical resistance at ULS could be taken as 1,200 kilonewtons. In accordance with the CHBDC, the geotechnical resistance at ULS was factored using a resistance factor of 0.4. |
| | <ul style="list-style-type: none">Post-construction settlement of the silty clay deposits due to embankment construction will result in downward movement of the soil around the piles induce downdrag forces on the piles through negative skin friction. The downdrag load will depend on pile type, pile dimensions, and pile material and should be considered during design.Pile caps should be provided with at least 1.8 metres of earth cover for frost protection purposes.For uplift resistance, the tensile capacity of the driven piles should be ignored. Therefore, if some form of uplift resistance will be required (e.g., tensioned rock anchors). |

Table 6.1 – Summary of Deep Foundation Alternatives at Trim Road (Continued)

| Foundation Alternative | Comments |
|---|---|
| Alternative 2: Socketed piles or caissons into sound bedrock | <ul style="list-style-type: none">Consideration could be given to founding the proposed structure on steel piles socketed and then grouted into bedrock (e.g., using the ODEX drilling system). Alternatively, large diameter concrete caissons socketed into bedrock could be considered. |
| | <ul style="list-style-type: none">For preliminary design and costing purposes, the geotechnical resistance at ULS of socketed piles or caissons that derive support only in shear within the bedrock could be calculated using an unfactored average shear resistance along the socket of about 1,000 kilopascals. The geotechnical reaction at SLS will be greater than the factored geotechnical resistance at ULS; as such, ULS conditions will govern. For socketed piles, the structural capacity of the pile will govern if it is less than the capacity derived from socket shear. |
| | <ul style="list-style-type: none">The capacity derived from socket shear could be used to provide both compression and uplift (tension) resistance. In accordance with the CHBDC, the geotechnical resistance at ULS should be factored using resistance factors of 0.4 and 0.3 for compression and tension, respectively. |
| | <ul style="list-style-type: none">Socketed micropiles or caissons that derive support in shear within the bedrock should have a nominal socket length to diameter ratio of at least 2 to 3. |
| | <ul style="list-style-type: none">Post-construction settlement of the silty clay deposits due to embankment construction will result in downward movement of the soil around the piles/caissons induce downdrag forces on the piles/caissons through negative skin friction. The downdrag load will depend on pile/caisson type, pile/caisson dimensions, and pile/caisson material and should be considered during design. |
| | <ul style="list-style-type: none">Pile caps (and caisson caps, if required) should be provided with at least 1.8 metres of earth cover for frost protection purposes. |

It is noted that the bedrock surface could be located up to 80 metres below ground surface. For this case, caisson construction may not be a viable alternative for the proposed underpass.

Based on the results of shear wave velocity testing that we have carried out for developments south of the Trim Road interchange, seismic Site Class E could be used for preliminary foundation design purposes. Site specific shear wave velocity testing should be carried out during the design stage to confirm the seismic Site Classification and evaluate whether a more favourable Site Class (i.e., Site Class D) can be specified. There is no potential for liquefaction of the overburden material at this site.

6.3.2 Approach Embankments

Approach embankments to the proposed underpass structure will be required. Although the height of the approach embankments is not presently known, preliminary considerations for embankment construction are provided below:

- All topsoil, organic material, and unsuitable fill material should be removed from the base of the embankments.
- The embankment fill material could consist of compacted material meeting OPSS Granular B Type I or II, OPSS Select Subgrade Material, or suitable, well graded and shattered blast rock.
- Final fill slopes constructed with OPSS Granular B Type I or Select Subgrade Material could be sloped at 2.5 horizontal to 1 vertical, or flatter; for Granular B Type II or well graded and shattered blast rock, fill slopes of 2.0 horizontal to 1 vertical, or flatter would be suitable. Where steeper embankment slopes are required due to space limitations, some form of retaining structure, such as a geogrid reinforced slope, a cast in place concrete wall, or a Mechanically Stabilized Earth (MSE) wall could be considered.
- The approach embankments will be underlain by deposits of sensitive silty clay which have a reduced capacity to support loads imposed by grade raise fill material. Based on the settlement history of previous embankments constructed on sensitive silty clay deposits in the Ottawa area, the estimated long-term settlement of 2 to 3 metre high embankments could be in the order of 100 to 200 millimetres. Since the approach embankments will likely be in the order of 7 metres high, the long-term settlement is expected to exceed settlement tolerances. Consideration could be given to:
 - Pre-loading the site could be considered to allow for the majority of the primary consolidation settlement of the silty clay deposits to occur prior to construction of the proposed embankments. Pre-loading could be carried out in conjunction with the use of wick drains to accelerate the rate of settlement. It is noted that secondary consolidation and settlement of the silty clay deposits will continue after the pre-loading material is removed from the site. This will result in some future settlement of the embankments.
 - The use of lightweight fill material (e.g., expanded polystyrene or slag fill) as part of the embankment construction in order to limit the stress increase on the underlying silty clay and reduce post-construction settlement.
- The settlement of the embankments would be entirely differential to the underpass structure. Furthermore, the design of the embankments must also consider the location of OR 174, the proposed Trim Road Station, and any adjacent services, and the impact that the settlements may have on that infrastructure.
- The overall stability of the embankment side slopes will depend on the geometry and composition of the approach embankments. However, to assess the feasibility of

embankment construction in this area, preliminary slope stability analyses were carried out. The results of the stability analyses indicate that 6 metre high approach embankments, with side slopes constructed at 2 to 2.5 horizontal to 1 vertical, would have an adequate factor of safety against a deep seated shear failure through the silty clay.

6.4 Impacts and Mitigation Measures

A summary of the possible construction and operational impacts in the area of the Trim Road interchange are summarized in Table 6.2.

Table 6.2 – Impacts and Mitigation Measures (Trim Road Interchange)

| Type | Impact(s) | Mitigation Measure(s) |
|-----------------------|---|---|
| Operational Impact(s) | <ul style="list-style-type: none">Differential settlement of the approach embankments will be entirely differential to the overpass structure.Depending on the location of OR 174, and any existing services, relative to the proposed embankments, construction of the approach embankments may result in post-construction settlement of OR 174, the proposed Trim Road Station and any adjacent services.Embankments that are greater than 2 to 3 metres in height could have long-term settlements in excess of 100 to 200 millimetres. | <ul style="list-style-type: none">Construction of approach slabs at the transition between the structure and embankments.Track re-ballasting could be a viable alternative to address the long-term settlements.If the estimated settlements cannot be tolerated, the use of lightweight fill material (e.g., expanded polystyrene or slag fill) as part of the embankment construction could be considered in order to limit the stress increase on the underlying silty clay and reduce post-construction settlement. Site pre-loading (with or without wick drains) could also be considered to reduce post-construction settlements; however, pre-loading would not mitigate the potential for settlement related impacts to OR 174 or any adjacent services. The estimated settlement of the embankments will be refined during detailed design. |
| | <ul style="list-style-type: none">Deep foundations, which derive their capacity from the underlying bedrock, are required for support of the proposed overpass structure. The location of the bedrock surface is presently unknown, but could be located up to 80 metres below ground surface. | <ul style="list-style-type: none">Various foundation alternatives are available. |

7.0 ADDITIONAL CONSIDERATIONS

7.1 Eastern LRT Stations

Stations will be constructed at various locations along the Eastern LRT alignment. For preliminary design and costing purposes, our comments on the proposed stations are provided in Table 7.1.

Table 7.1 – Preliminary Design Information for the Transit Stations

| Station | Anticipated Subsurface Conditions | Most Probable Foundation Type | Factored Net Geotechnical Reaction at SLS (kPa) | Factored Net Geotechnical Resistance at ULS (kPa) | Comments |
|-------------------|-----------------------------------|-------------------------------|---|---|---|
| Montreal | Silty Clay | Deep Foundations | Refer to Table 4.3 | Refer to Table 4.3 | <ul style="list-style-type: none">The station will be located about 4 to 10 metres above existing grade.It is likely that a portion of the station will be founded on the approach embankment and a portion carried by the overpass structure.Given that significant settlement of the approach fills should be anticipated, deep foundations are likely for the west portion of the station structure. |
| Jeanne D'Arc | Silty Clay | Spread Footings | 100 to 125 | 200 to 250 | <ul style="list-style-type: none">No significant grade raise required. It is anticipated that the footings will be founded directly on native soil. |
| Orleans Boulevard | Silty Clay | Spread Footings | 100 to 125 | 200 to 250 | <ul style="list-style-type: none">No significant grade raise required. It is anticipated that the footings will be founded directly on native soil. |
| Place D'Orleans | Glacial Till or Bedrock | Spread Footings | 150 (Till) | 300 (Till) 1500 (Bedrock) | <ul style="list-style-type: none">No significant grade raise required. It is anticipated that the footings will be founded directly on native soil or bedrock. |

Table 7.1 – Preliminary Design Information for the Transit Stations (Continued)

| Station | Anticipated Subsurface Conditions | Most Probable Foundation Type | Factored Net Geotechnical Reaction at SLS (kPa) | Factored Net Geotechnical Resistance at ULS (kPa) | Comments |
|---------------------|-----------------------------------|-------------------------------|---|---|--|
| Orleans Town Centre | Silty Clay | Spread Footings | 100 to 125 | 200 to 250 | <ul style="list-style-type: none">No significant grade raise required. It is anticipated that the footings will be founded directly on native soil. |
| Tenth Line Station | Silty Clay | Spread Footings | 100 to 125 | 200 to 250 | <ul style="list-style-type: none">No significant grade raise required. It is anticipated that the footings will be founded directly on native soil. |
| Trim Station | Silty Clay | Spread Footings | 100 to 125 | 200 to 250 | <ul style="list-style-type: none">No significant grade raise required. It is anticipated that the footings will be founded directly on native soil or bedrock. |

The silty clay deposits along the Eastern LRT alignment are highly susceptible to frost heaving when exposed to freezing temperatures. The footings/caps should be provided with at least 1.8 metres of earth cover for frost protection purposes. Alternatively, the required frost protection could be provided by means of a combination of earth cover and extruded polystyrene insulation. Furthermore, in order to avoid differential frost heaving between the station platforms and tracks, the subgrade surface below the tracks, within the stations, could be protected from frost using extruded polystyrene insulation. Transitions tapers will be required where the extruded polystyrene insulation is terminated beyond the stations.

7.2 Culvert Crossings

The proposed Eastern LRT alignment will cross structural culverts at the Jasmine Park Ravine, Green’s Creek, Bilberry Creek, and Taylor Creek. Any culverts that are reaching the end of their service life should be rehabilitated/replaced prior to the Eastern LRT construction.

7.3 Track Bed

The track ballast and subballast should be appropriately designed for the sensitive silty clay deposits along the proposed alignment. Frost tapers will be required where the track bed transitions between different subgrade materials (e.g., from silty clay to glacial till). Other transition treatments may be required; for example, where the subgrade abruptly changes from overburden to bedrock, it may be necessary to “cushion” the transition by replacing the upper part of the bedrock in the area of the transition with granular material.

Adequate drainage of the ballast/subballast materials is important for the long term performance of the track bed. In order to provide drainage of the subballast, it is suggested that subdrains be installed in areas where the Eastern LRT will be in cut section and in areas where the Eastern LRT will be located between the east and westbound lanes of OR 174.

7.4 Vibrations

Rail lines can produce levels of ground vibrations that may be perceptible at nearby buildings. The vibration levels felt at nearby buildings will depend on the subsurface conditions in the area. If significant, vibrations could affect the liveability of adjacent buildings and some form of vibration isolation may be required. Vibration impact studies should be carried out early in the planning process for the Eastern LRT.

7.5 Noise Wall and Lighting Foundations

It is anticipated that any standard low height noise wall/lighting foundations will consist of augered concrete piers completed in native deposits of silty clay or glacial till. It is noted cobble and boulders obstructions may be encountered within the glacial till. As such, it may be necessary to remove/break any boulders encountered during augering. To minimize disturbance to the sensitive silty clay deposits, foundation construction within silty clay using vibratory methods should be avoided. Where bedrock is encountered, socketed piers or spread footing foundations (with or without anchors to resist overturning) may be required.

High mast lighting, where required, will likely require some form of deep foundation to resist overturning (e.g., concrete caissons).

7.6 Additional Investigation and Comments

This report provides preliminary geotechnical guidelines, and our interpretation of the construction/operations impacts, for the project based on available sources of information. Detailed geotechnical investigations should be carried out as part of the final design and detailed costing.

We trust that this report is sufficient for your current requirements. If you have any questions concerning this information or if we can be of further assistance to you on this project, please call.



Johnathan A. Cholewa, Ph.D., P.Eng.





Andrew Chevrier, M.Eng., P.Eng.
Principal




APPENDIX A

Proposed Eastern LRT Plan and Profile (Sheets 1 to 22)



NOTES:





- LEGEND:
- PROPOSED LRT CORRIDOR
 - PROPOSED LRT
 - PROPOSED LRT STATIONS
 - PROPOSED WIDENING
 - PROPOSED LANE ALIGNMENT
 - EXISTING ROADWAY
 - WATERCOURSES
 - PROPERTY LIMITS
 - WATERMAIN

PARSONS

| | | |
|--|-----------------------|---------------|
| Date: JULY 2015 | Designed By: | Drawn By: |
| Project Manager: | Discipline Engineer: | Checked By: |
| Scale: 0m 10 20 50 100 0m 2.5 5 10 20 HORIZONTAL VERTICAL | | |
| CAD File Name: TO3175TOC-01-ELRT-01.DGN | Plot Date: XX/XX/XXXX | Drawings No.: |

Ottawa

EASTERN LRT
STA. 300+000 to STA 313+000



NOTES:

KEY PLAN

LEGEND:

- PROPOSED LRT CORRIDOR
- PROPOSED LRT STATIONS
- PROPOSED WIDENING
- PROPOSED LANE ALIGNMENT
- EXISTING ROADWAY
- WATERCOURSES
- PROPERTY LIMITS
- WATERMAIN

PARSONS

| | | |
|------------------|----------------------|-------------|
| Date: JULY 2015 | Designed By: | Drawn By: |
| Project Manager: | Discipline Engineer: | Checked By: |



Scale: 0m 10 20 50 100
0m 2.5 5 10 20
HORIZONTAL
VERTICAL

CAD File Name: TO3175TOC- 01-ELRT-03.DGN Plot Date: XX/XX/XXXX


Ottawa

EASTERN LRT
STA. 301+000 to STA 301+600

| | | |
|---------------|-------------|--------------|
| Drawings No.: | Revision 00 | Sheet No. 03 |
|---------------|-------------|--------------|



NOTES:



- LEGEND:
- PROPOSED LRT CORRIDOR
 - PROPOSED LRT
 - PROPOSED LRT STATIONS
 - PROPOSED WIDENING
 - PROPOSED LANE ALIGNMENT
 - EXISTING ROADWAY
 - WATERCOURSES
 - PROPERTY LIMITS
 - WATERMAIN


PARSONS

| | | |
|---|-----------------------|-------------|
| Date: JULY 2015 | Designed By: | Drawn By: |
| Project Manager: | Discipline Engineer: | Checked By: |
| Scale: 0m 10 20 50 100 0m 2.5 5 10 20 HORIZONTAL VERTICAL | | |
| CAD File Name: TO3175TOC-01-ELRT-04.DGN | Plot Date: XX/XX/XXXX | |




EASTERN LRT
STA. 301+600 to STA 302+200

| | | |
|---------------|--------------|---------------|
| Drawings No.: | Revision: 00 | Sheet No.: 04 |
|---------------|--------------|---------------|



NOTES:





- LEGEND:
- PROPOSED LRT CORRIDOR
 - PROPOSED LRT
 - PROPOSED LRT STATIONS
 - PROPOSED WIDENING
 - PROPOSED LANE ALIGNMENT
 - EXISTING ROADWAY
 - WATERCOURSES
 - PROPERTY LIMITS
 - WATERMAIN


| | | |
|--|-----------------------|-------------|
| Date: JULY 2015 | Designed By: | Drawn By: |
| Project Manager: | Discipline Engineer: | Checked By: |
| Scale: 0m 10 20 50 100 0m 2.5 5 10 20 HORIZONTAL VERTICAL | | |
| CAD File Name: TO3175TOD-01-ELRT-05.DGN | Plot Date: XX/XX/XXXX | |

EASTERN LRT
STA. 302+200 to STA 302+800

Drawings No.: 00 Revision 05 Sheet No. 05



NOTES:



- LEGEND:
- PROPOSED LRT CORRIDOR
 - PROPOSED LRT
 - PROPOSED LRT STATIONS
 - PROPOSED WIDENING
 - PROPOSED LANE ALIGNMENT
 - EXISTING ROADWAY
 - WATERCOURSES
 - PROPERTY LIMITS
 - WATERMAIN



PARSONS

| | | | |
|------------------|--|----------------------|-------------|
| Date: | JULY 2015 | Designed By: | Drawn By: |
| Project Manager: | | Discipline Engineer: | Checked By: |
| Scale: | <div>0m 10 20 50 100</div> <div>0m 2.5 5 10 20</div> <div>HORIZONTAL</div> <div>VERTICAL</div> | | |
| CAD File Name: | T03175T0C- 01-ELRT-06.DGN | | |
| Plot Date: | XX/XX/XXXX | | |


Ottawa

EASTERN LRT
STA. 302+800 to STA 303+400

| | | |
|---------------|----------|-----------|
| Drawings No.: | Revision | Sheet No. |
| | 00 | 06 |



NOTES:



- LEGEND:
- PROPOSED LRT CORRIDOR
 - PROPOSED LRT STATIONS
 - PROPOSED WIDENING
 - PROPOSED LANE ALIGNMENT
 - EXISTING ROADWAY
 - WATERCOURSES
 - PROPERTY LIMITS
 - WATERMAIN



PARSONS

| | | |
|--|-----------------------|---------------|
| Date: JULY 2015 | Designed By: | Drawn By: |
| Project Manager: | Discipline Engineer: | Checked By: |
| Scale: 0m 10 20 50 100 0m 2.5 5 10 20 HORIZONTAL VERTICAL | | |
| CAD File Name: TO3175TOC-01-ELRT-07.DGN | Plot Date: XX/XX/XXXX | Drawings No.: |


Ottawa

EASTERN LRT
STA. 302+400 to STA 304+000

Revision 00 Sheet No. 07



NOTES:



- LEGEND:
- PROPOSED LRT CORRIDOR
 - PROPOSED LRT
 - PROPOSED LRT STATIONS
 - PROPOSED WIDENING
 - PROPOSED LANE ALIGNMENT
 - EXISTING ROADWAY
 - WATERCOURSES
 - PROPERTY LIMITS
 - WATERMAIN



PARSONS

| | | |
|------------------|---------------------------|-------------|
| Date: | DESIGNED BY: | DRAWN BY: |
| JULY 2015 | | |
| Project Manager: | Discipline Engineer: | Checked By: |
| | | |
| Scale: | HORIZONTAL | |
| | 0m 10 20 50 100 | |
| | VERTICAL | |
| | 0m 2.5 5 10 20 | |
| CAD File Name: | TO3175TOC- 01-ELRT-08.DGN | |
| Plot Date: | XX/XX/XXXX | |


Ottawa

EASTERN LRT
STA. 304+000 to STA 304+600

| | | |
|---------------|----------|-----------|
| Drawings No.: | Revision | Sheet No. |
| | 00 | 08 |



NOTES:





- LEGEND:
- PROPOSED LRT CORRIDOR
 - PROPOSED LRT STATIONS
 - PROPOSED LRT WIDENING
 - PROPOSED LANE ALIGNMENT
 - EXISTING ROADWAY
 - WATERCOURSES
 - PROPERTY LIMITS
 - WATERMAIN
 - HYDRO CENTRELINE
 - HYDRO CORRIDOR
 - EXISTING HYDRO POLES

PARSONS


| | | |
|--|-----------------------|-------------|
| Date: JULY 2015 | Designed By: | Drawn By: |
| Project Manager: | Discipline Engineer: | Checked By: |
| Scale: 0m 10 20 50 100 0m 2.5 5 10 20 HORIZONTAL VERTICAL | | |
| CAD File Name: TO3175TOC-01-ELRT-09.DGN | Plot Date: XX/XX/XXXX | |

EASTERN LRT
STA. 304+600 to STA 305+200

| | | |
|---------------|--------------|---------------|
| Drawings No.: | Revision: 00 | Sheet No.: 09 |
|---------------|--------------|---------------|



NOTES:



- LEGEND:
- PROPOSED LRT CORRIDOR
 - PROPOSED LRT STATIONS
 - PROPOSED LANE ALIGNMENT
 - EXISTING ROADWAY
 - WATERCOURSES
 - PROPERTY LIMITS
 - WATERMAIN
 - HYDRO CENTRELINE
 - HYDRO CORRIDOR
 - EXISTING HYDRO POLES

PARSONS













| | | |
|------------------|--------------------------|-------------|
| Date: | DESIGNED BY: | DRAWN BY: |
| JULY 2015 | | |
| Project Manager: | Discipline Engineer: | Checked By: |
| | | |
| Scale: | HORIZONTAL | |
| | 0m 10 20 50 100 | |
| | VERTICAL | |
| | 0m 2.5 5 10 20 | |
| CAD File Name: | TO3175TOC-01-ELRT-10.DGN | |
| Plot Date: | XX/XX/XXXX | |


Ottawa

EASTERN LRT
STA. 305+200 to STA 305+800



| | | |
|---------------|----------|-----------|
| Drawings No.: | Revision | Sheet No. |
| | 00 | 10 |




- | | | | |
|---|-------------------------|---|----------------------|
|  | PROPOSED LRT CORRIDOR |  | EXISTING ROADWAY |
|  | PROPOSED LRT |  | WATERCOURSES |
|  | PROPOSED LRT STATIONS |  | PROPERTY LIMITS |
|  | PROPOSED WIDENING |  | WATERMAIN |
|  | PROPOSED LANE ALIGNMENT |  | HYDRO CENTRELINE |
| | |  | HYDRO CORRIDOR |
| | |  | EXISTING HYDRO POLES |



| | | | |
|---|---------------|----------------|-----------------|
| X | Drawings No.: | Revision 00 | Sheet No. 11 |
|---|---------------|----------------|-----------------|



NOTES:




- LEGEND:
- PROPOSED LRT CORRIDOR
 - PROPOSED LRT
 - PROPOSED LRT STATIONS
 - PROPOSED WIDENING
 - PROPOSED LANE ALIGNMENT
 - EXISTING ROADWAY
 - WATERCOURSES
 - PROPERTY LIMITS
 - WATERMAIN
 - HYDRO CENTRELIN
 - HYDRO CORRIDOR
 - EXISTING HYDRO POLES

PARSONS


| | | |
|--|-----------------------|-------------|
| Date: JULY 2015 | Designed By: | Drawn By: |
| Project Manager: | Discipline Engineer: | Checked By: |
| Scale: 0m 10 20 50 100 0m 2.5 5 10 20 HORIZONTAL VERTICAL | | |
| CAD File Name: TO3175TOC-01-ELRT-12.DGN | Plot Date: XX/XX/XXXX | |

EASTERN LRT
STA. 306+400 to STA 307+000

| | | |
|---------------|-------------|--------------|
| Drawings No.: | Revision 00 | Sheet No. 12 |
|---------------|-------------|--------------|



NOTES:



- LEGEND:
- PROPOSED LRT CORRIDOR
 - PROPOSED LRT STATIONS
 - PROPOSED LRT WIDENING
 - PROPOSED LANE ALIGNMENT
 - EXISTING ROADWAY
 - WATERCOURSES
 - PROPERTY LIMITS
 - WATERMAIN
 - HYDRO CENTRELINE
 - HYDRO CORRIDOR
 - EXISTING HYDRO POLES



PARSONS

| | | | | | |
|------------------|--|----------------------|--|-------------|--|
| Date: | JULY 2015 | Designed By: | | Drawn By: | |
| Project Manager: | | Discipline Engineer: | | Checked By: | |
| Scale: | <div><div>0m102050100</div><div>0m2.551020</div><div>HORIZONTAL</div><div>VERTICAL</div></div> | | | | |
| CAD File Name: | T03175TOD-01-ELRT-13.DGN | | | | |
| | Plot Date: XX/XX/XXXX | | | | |


Ottawa

EASTERN LRT
STA. 306+400 to STA 307+600

| | | |
|---------------|----------|-----------|
| Drawings No.: | Revision | Sheet No. |
| | 00 | 13 |



NOTES:





- LEGEND:
- PROPOSED LRT CORRIDOR
 - PROPOSED LRT
 - PROPOSED LRT STATIONS
 - PROPOSED WIDENING
 - PROPOSED LANE ALIGNMENT
 - EXISTING ROADWAY
 - WATERCOURSES
 - PROPERTY LIMITS
 - WATERMAIN
 - HYDRO CENTRELINE
 - HYDRO CORRIDOR
 - EXISTING HYDRO POLES

PARSONS


| | | |
|--|-----------------------|-------------|
| Date: JULY 2015 | Designed By: | Drawn By: |
| Project Manager: | Discipline Engineer: | Checked By: |
| Scale: 0m 10 20 50 100 0m 2.5 5 10 20 HORIZONTAL VERTICAL | | |
| CAD File Name: TO3175TOC-01-ELRT-14.DGN | Plot Date: XX/XX/XXXX | |

EASTERN LRT
STA. 307+600 to STA 308+200

| | | |
|---------------|-------------|--------------|
| Drawings No.: | Revision 00 | Sheet No. 14 |
|---------------|-------------|--------------|



NOTES:



- LEGEND:
- PROPOSED LRT CORRIDOR
 - PROPOSED LRT
 - PROPOSED LRT STATIONS
 - PROPOSED WIDENING
 - PROPOSED LANE ALIGNMENT
 - EXISTING ROADWAY
 - WATERCOURSES
 - PROPERTY LIMITS
 - WATERMAIN
 - HYDRO CENTRELINE
 - HYDRO CORRIDOR
 - EXISTING HYDRO POLES

PARSONS

| | | |
|------------------|----------------------|-------------|
| Date: JULY 2015 | Designed By: | Drawn By: |
| Project Manager: | Discipline Engineer: | Checked By: |



Scale: 0m 10 20 50 100
0m 2.5 5 10 20
HORIZONTAL
VERTICAL

CAD File Name: T03175TOD-01-ELRT-15.DGN


Plot Date: XX/XX/XXXX

EASTERN LRT
STA. 308+200 to STA 308+800

| | | |
|---------------|--------------|---------------|
| Drawings No.: | Revision: 00 | Sheet No.: 15 |
|---------------|--------------|---------------|



NOTES:





- LEGEND:
- PROPOSED LRT CORRIDOR
 - PROPOSED LRT
 - PROPOSED LRT STATIONS
 - PROPOSED WIDENING
 - PROPOSED LANE ALIGNMENT
 - EXISTING ROADWAY
 - WATERCOURSES
 - PROPERTY LIMITS
 - WATERMAIN
 - HYDRO CENTRELINE
 - HYDRO CORRIDOR
 - EXISTING HYDRO POLES


| | | |
|---|----------------------|--------------------------|
| Date: JULY 2015 | Designed By: | Drawn By: |
| Project Manager: | Discipline Engineer: | Checked By: |
| Scale: 0m 10 20 50 100 0m 2.5 5 10 20 HORIZONTAL VERTICAL | | |
| CAD File Name: TO3175TOC- 01-ELRT-16.DGN | | Plot Date: XX/XX/XXXX |

EASTERN LRT
STA. 308+800 to STA 309+400

| | | |
|---------------|----------------|-----------------|
| Drawings No.: | Revision 00 | Sheet No. 16 |
|---------------|----------------|-----------------|



NOTES:



- LEGEND:
- PROPOSED LRT CORRIDOR
 - PROPOSED LRT
 - PROPOSED LRT STATIONS
 - PROPOSED WIDENING
 - PROPOSED LANE ALIGNMENT
 - EXISTING ROADWAY
 - WATERCOURSES
 - PROPERTY LIMITS
 - WATERMAIN
 - HYDRO CENTRELINE
 - HYDRO CORRIDOR
 - EXISTING HYDRO POLES


PARSONS

| | | |
|------------------|--------------------------|-------------|
| Date: | DESIGNED BY: | DRAWN BY: |
| JULY 2015 | | |
| Project Manager: | Discipline Engineer: | Checked By: |
| | | |
| Scale: | HORIZONTAL | |
| | 0m 10 20 50 100 | |
| | VERTICAL | |
| | 0m 2.5 5 10 20 | |
| CAD File Name: | T03175TOD-01-ELRT-17.DGN | |
| Plot Date: | XX/XX/XXXX | |


Ottawa

EASTERN LRT
STA. 309+400 to STA 310+000

| | | |
|---------------|----------|-----------|
| Drawings No.: | Revision | Sheet No. |
| | 00 | 17 |



NOTES:



- LEGEND:
- PROPOSED LRT CORRIDOR
 - PROPOSED LRT
 - PROPOSED LRT STATIONS
 - PROPOSED WIDENING
 - PROPOSED LANE ALIGNMENT
 - EXISTING ROADWAY
 - WATERCOURSES
 - PROPERTY LIMITS
 - WATERMAIN
 - HYDRO CENTRELINE
 - HYDRO CORRIDOR
 - EXISTING HYDRO POLES

PARSONS

| | | |
|------------------|----------------------------|-------------|
| Date: | DESIGNED BY: | DRAWN BY: |
| JULY 2015 | | |
| Project Manager: | Discipline Engineer: | Checked By: |
| | | |
| Scale: | HORIZONTAL | |
| | 0m 10 20 50 100 | |
| | VERTICAL | |
| | 0m 2.5 5 10 20 | |
| CAD File Name: | T031751TOD-01-ELRT-17A.DGN | |
| Plot Date: | XX/XX/XXXX | |

Ottawa

EASTERN LRT
STA. 309+400 to STA 310+000

| | | |
|---------------|----------|-----------|
| Drawings No.: | Revision | Sheet No. |
| | 00 | 17A |



KEY PLAN

HWY OR174

ST. JOSEPH

MONTREAL RD

BLAIR RD













JEANNE D'ARC


ORLEANS BLVD

CHAMPLAIN ST.



TENTH LINE RD

TRM RD


- | | | | |
|---|-------------------------|---|----------------------|
|  | PROPOSED LRT CORRIDOR |  | EXISTING ROADWAY |
|  | PROPOSED LRT |  | WATERCOURSES |
|  | PROPOSED LRT STATIONS |  | PROPERTY LIMITS |
|  | PROPOSED WIDENING |  | WATERMAIN |
|  | PROPOSED LANE ALIGNMENT |  | HYDRO CENTRELINE |
| | |  | HYDRO CORRIDOR |
| | |  | EXISTING HYDRO POLES |



| | | |
|---------------|----------------|-----------------|
| Drawings No.: | Revision 00 | Sheet No. 18 |
|---------------|----------------|-----------------|



NOTES:



- LEGEND:
- PROPOSED LRT CORRIDOR
 - PROPOSED LRT
 - PROPOSED LRT STATIONS
 - PROPOSED WIDENING
 - PROPOSED LANE ALIGNMENT
 - EXISTING ROADWAY
 - WATERCOURSES
 - PROPERTY LIMITS
 - WATERMAIN
 - HYDRO CENTRELINE
 - HYDRO CORRIDOR
 - EXISTING HYDRO POLES

PARSONS

| | | |
|------------------|----------------------|-------------|
| Date: JULY 2015 | Designed By: | Drawn By: |
| Project Manager: | Discipline Engineer: | Checked By: |



Scale: 0m 10 20 50 100
0m 2.5 5 10 20
HORIZONTAL
VERTICAL

CAD File Name: TO3175TOC-01-ELRT-19.DGN


Plot Date: XX/XX/XXXX

EASTERN LRT
STA. 310+000 to STA 310+600

| | | |
|---------------|-------------|--------------|
| Drawings No.: | Revision 00 | Sheet No. 19 |
|---------------|-------------|--------------|



NOTES:



- LEGEND:
- PROPOSED LRT CORRIDOR
 - PROPOSED LRT
 - PROPOSED LRT STATIONS
 - PROPOSED WIDENING
 - PROPOSED LANE ALIGNMENT
 - EXISTING ROADWAY
 - WATERCOURSES
 - PROPERTY LIMITS
 - WATERMAIN
 - HYDRO CENTRELINE
 - HYDRO CORRIDOR
 - EXISTING HYDRO POLES

PARSONS

| | | |
|------------------|----------------------|-------------|
| Date: JULY 2015 | Designed By: | Drawn By: |
| Project Manager: | Discipline Engineer: | Checked By: |

Scale: 0m 10 20 50 100
0m 2.5 5 10 20
HORIZONTAL
VERTICAL



CAD File Name: TO3175TOC-01-ELRT-20.DGN

Plot Date: XX/XX/XXXX


Ottawa

EASTERN LRT
STA. 311+200 to STA 311+800

| | | |
|---------------|-------------|--------------|
| Drawings No.: | Revision 00 | Sheet No. 20 |
|---------------|-------------|--------------|



NOTES:





- LEGEND:
- PROPOSED LRT CORRIDOR
 - PROPOSED LRT STATIONS
 - PROPOSED LRT STATIONS
 - PROPOSED WIDENING
 - PROPOSED LANE ALIGNMENT
 - EXISTING ROADWAY
 - WATERCOURSES
 - PROPERTY LIMITS
 - WATERMAIN
 - HYDRO CENTRELINE
 - HYDRO CORRIDOR
 - EXISTING HYDRO POLES

PARSONS

| | | |
|--|-----------------------|-------------|
| Date: JULY 2015 | Designed By: | Drawn By: |
| Project Manager: | Discipline Engineer: | Checked By: |
| Scale: 0m 10 20 50 100 0m 2.5 5 10 20 HORIZONTAL VERTICAL | | |
| CAD File Name: TO3175TOC-01-ELRT-21.DGN | Plot Date: XX/XX/XXXX | |


EASTERN LRT
STA. 311+800 to STA 312+400

| | | |
|---------------|--------------|--------------|
| Drawings No.: | Revision: 00 | Sheet No. 21 |
|---------------|--------------|--------------|



| | | |
|---|----------------|-----------------|
|  | | |
| <p>EASTERN LRT STA. 312+400 to STA 313+000</p> | | |
| Drawings No.: | Revision 00 | Sheet No. 22 |

Blair Road Interchange Relevant Borehole Logs by Others



SAMPLER HAMMER, 83.6kg, DROP, 760mm

PENETRATION TEST HAMMER: 83.5kg DROP: 760mm

W.L. in
Standpipe at
Elev. 74.28
May. 5, 1987

1 : 26

CHECKED *AC*

Golder Associates

SAMPLER, HAMMER, 63.6kg, DROP, 760mm

PENETRATION TEST HAMMER: 63.5kg DBOP: 760mm

Org = 67.3 %

W.L. in Open
Hole at
Elev. 73.91
May. 6, 1987

1 : 25

CHECKED *AC*

Golder Associates

| RECORD OF BOREHOLE 29 | | | | | | | | | | | | SHEET 1 of 1 | | | |
|--------------------------------------|--|--|---|---|----------|---|---------------------------|--|------------------------|----------------------------|---|-------------------|--|--|--|
| LOCATION: See Figure 2 | | | | BORING DATE: April 27, 1987 | | | | DATUM: GEODETIC | | | | | | | |
| SAMPLER: HAMMER, 63.5kg, DROP: 760mm | | | | PENETRATION TEST: HAMMER, 63.5kg, DROP: 760mm | | | | | | | | | | | |
| DEPTH SCALE METRES | BORING METHOD | SOIL PROFILE | | SAMPLES | | DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m | | HYDRAULIC CONDUCTIVITY, k, CM/SEC | | ADDITIONAL LAB. TESTING | PIEZOMETER OR STANDPIPE INSTALLATION | | | | |
| | | DESCRIPTION | STRATA PLOT ELEV. DEPTH (M) | NUMBER | TYPE | BLOWS/0.3M | SHEAR STRENGTH Cu, kPa | nat.V. - + Q. - ● rem.V. - ⊗ U. - ○ | WATER CONTENT, PERCENT | | | | | | |
| 0 | Power Auger 200mm Diam. (Hollow Stem) | Ground Surface | 74.67 | | | | | | | | | | | | |
| | | TOPSOIL | 0.00 | | | | | | | | | | | | |
| | | | 0.09 | | | | | | | | | | | | |
| | | Brown sandy silt, some gravel and clay (FILL) | | | | | | | | | | | | | |
| | | | 74.16 | | | | | | | | | | | | |
| | | TOPSOIL | 0.52 | | | | | | | | | | | | |
| | | | 73.94 | | | | | | | | | | | | |
| | | | 0.73 | | | | | | | | | | | | |
| 1 | | | | | 1 | 50 DO | 9 | | | | | | | | |
| 2 | | | Loose to very dense brown to grey sandy silt, some gravel and shale fragments, trace clay (GLACIAL TILL) | | 2 | 50 DO | 55 | | | | | | | | |
| 3 | | | | 3 | 50 DO | 25 | | | | | | | | | |
| | | | | 4 | 50 DO | 25 | | | | | | | | | |
| | | Weathered SHALE BEDROCK | 71.32 | | | | | | | | | | | | |
| | | End of Hole | 3.41 | | | | | | | | | | | | |
| | | Auger Refusal | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | |
| DEPTH SCALE | | | | | | | | | | | | LOGGED S.L. | | | |
| 1 : 25 | | | | | | | | | | | | Golder Associates | | | |
| | | | | | | | | | | | | CHECKED AC | | | |

| RECORD OF BOREHOLE 32 | | | | | | | | | | | | SHEET 1 of 1 | | | |
|--------------------------------------|--|---|---|---|----------|---|---------------------------|--|------------------------|----------------------------|---|-------------------|--|--|--|
| LOCATION: See Figure 2 | | | | BORING DATE: April 30, 1987 | | | | DATUM: GEODETIC | | | | | | | |
| SAMPLER: HAMMER, 63.5kg, DROP: 760mm | | | | PENETRATION TEST: HAMMER, 63.5kg, DROP: 760mm | | | | | | | | | | | |
| DEPTH SCALE METRES | BORING METHOD | SOIL PROFILE | | SAMPLES | | DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m | | HYDRAULIC CONDUCTIVITY, k, CM/SEC | | ADDITIONAL LAB. TESTING | PIEZOMETER OR STANDPIPE INSTALLATION | | | | |
| | | DESCRIPTION | STRATA PLOT ELEV. DEPTH (M) | NUMBER | TYPE | BLOWS/0.3M | SHEAR STRENGTH Cu, kPa | nat.V. - + Q. - ● rem.V. - ⊗ U. - ○ | WATER CONTENT, PERCENT | | | | | | |
| 0 | Power Auger 200mm Diam. (Hollow Stem) | Ground Surface | 76.32 | | | | | | | | | | | | |
| | | TOPSOIL | 76.00 | | | | | | | | | | | | |
| | | | 0.09 | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| 1 | | | Very loose brown sandy silt, some gravel and clay (FILL) | | 1 | 50 DO | 4 | | | | | | | | |
| | | | | | | | | | | | | | | | |
| 2 | | Compact to dense brown sandy silt, some gravel, trace clay occasional silty sand pocket (GLACIAL TILL) | | 2 | 50 DO | 35 | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | Weathered SHALE BEDROCK | 74.10 | | | | | | | | | | | | |
| | | End of Hole | 2.22 | | | | | | | | | | | | |
| | | Auger Refusal | 2.28 | | | | | | | | | | | | |
| 3 | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | |
| DEPTH SCALE | | | | | | | | | | | | LOGGED S.L. | | | |
| 1 : 25 | | | | | | | | | | | | Golder Associates | | | |
| | | | | | | | | | | | | CHECKED AC | | | |

W.L. in Open
Hole at
Elev. 75.60
May 5, 1987

SAMPLER HAMMER, 83.6kg, DROP, 760mm

PENETRATION TEST HAMMER, 83.6kg, DROP, 780mm

1 : 25

LOGGED S.Leighton

CHECKED

Golder Associates

SAMPLER HAMMER, 63.5kg, DROP, 760mm


PENETRATION TEST HAMMER, 83.5kg, DROP, 780mm

Backfill

Core material

Foundation material

W.L. in

W.L. in 
Standpipe at
Elev. 77.59
Aug. 18, 1987


DEPTH SCALE

1 : 25

LOGGED J.COBISA


CHECKED *[Signature]*

Golder Associates


| RECORD OF BOREHOLE 41 | | | | | | | | | | | | SHEET 1 of 1 | |  | |
|-------------------------------------|---|---|---|---------|-------|---|----------------------------------|--------------------------------------|--|----------------------------|---|--|--|---|--|
| LOCATION: See Figure 2 | | | | | | | | | | | | BORING DATE: Dec. 10, 1987 | | DATUM: GEODETIC | |
| SAMPLER HAMMER, 63.5kg, DROP: 760mm | | | | | | | | | | | | PENETRATION TEST HAMMER, 63.5kg, DROP: 760mm | | | |
| DEPTH SCALE METRES | BORING METHOD | SOIL PROFILE | | SAMPLES | | DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m | | HYDRAULIC CONDUCTIVITY, k, CM/SEC | | ADDITIONAL LAB. TESTING | PIEZOMETER OR STANDPIPE INSTALLATION | | | | |
| | | DESCRIPTION | STRATA PLOT ELEV. DEPTH (M) | NUMBER | TYPE | SHEAR STRENGTH Cu, kPa nat.V.- + Q.- ● rem.V.- ⊗ U.- ○ | WATER CONTENT, PERCENT Wp W U | | | | | | | | |
| 0 | Power Auger 200mm Diam (Hollow Stem) | Ground Surface | 75.28 | | | | | | | | | | | | |
| | | TOPSOIL | 0.00 0.06 | | | | | | | | | | | | |
| | | | | 1 | 50 DO | 7 | | | | | | | | | |
| 1 | | | Loose grey brown sandy silt, trace gravel and clay, trace organic matter (FILL) | | | | | | | | | | | | |
| | | | | 2 | 50 DO | 7 | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| 2 | | Compact grey brown silty sand some gravel and shale fragments, trace clay (GLACIAL TILL) | 73.88 1.40 | 3 | 50 DO | 12 | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| 3 | | Dense grey silty sand, some gravel and shale fragments, occasional cobble and boulder (GLACIAL TILL) | 72.69 2.59 | 4 | 50 DO | 39 | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | Weathered dark grey SHALE BEDROCK | 72.08 3.20 71.93 | 5 | 50 DO | > 50 | | | | | | | | | |
| | | End of Hole | 3.35 | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | |

DEPTH SCALE
1 : 25

Golder Associates


LOGGED S.Leighton
CHECKED 

0
15 6 PERCENT AXIAL STRAIN AT FAILURE
10

| RECORD OF BOREHOLE 42 | | | | | | | | | | | | SHEET 1 of 1 | |  | |
|-------------------------------------|---|--|--|---------|-------|---|----------------------------------|--------------------------------------|--|----------------------------|---|--|--|---|--|
| LOCATION: See Figure 2 | | | | | | | | | | | | BORING DATE: Dec. 10, 1987 | | DATUM: GEODETIC | |
| SAMPLER HAMMER, 63.5kg, DROP: 760mm | | | | | | | | | | | | PENETRATION TEST HAMMER, 63.5kg, DROP: 760mm | | | |
| DEPTH SCALE METRES | BORING METHOD | SOIL PROFILE | | SAMPLES | | DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m | | HYDRAULIC CONDUCTIVITY, k, CM/SEC | | ADDITIONAL LAB. TESTING | PIEZOMETER OR STANDPIPE INSTALLATION | | | | |
| | | DESCRIPTION | STRATA PLOT ELEV. DEPTH (M) | NUMBER | TYPE | SHEAR STRENGTH Cu, kPa nat.V.- + Q.- ● rem.V.- ⊗ U.- ○ | WATER CONTENT, PERCENT Wp W U | | | | | | | | |
| 0 | Power Auger 200mm Diam (Hollow Stem) | Ground Surface | 75.08 | | | | | | | | | | | | |
| | | | 0.00 | | | | | | | | | | | | |
| | | | | 1 | 50 DO | 4 | | | | | | | | | |
| | | | Loose to compact brown sandy silt, some gravel, trace clay rootlets and organic matter (FILL) | | | | | | | | | | | | |
| 1 | | | | 2 | 50 DO | 11 | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| 2 | | Compact grey brown silty sand some gravel, trace clay, occasional cobble and boulder (GLACIAL TILL) | 73.71 1.37 | 3 | 50 DO | 10 | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| 3 | | | 72.18 2.90 | 4 | 50 DO | 20 | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | Compact grey sandy silt, some gravel and shale fragments, trace clay (GLACIAL TILL) | 72.18 2.90 | 5 | 50 DO | 25 | | | | | | | | | |
| | | End of Hole | 71.42 3.66 | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | |

DEPTH SCALE
1 : 25

Golder Associates

LOGGED S.Leighton
CHECKED 

0
15 6 PERCENT AXIAL STRAIN AT FAILURE
10

SAMPLER HAMMER, 83.5kg, DROP, 760mm

PENETRATION TEST HAMMER, 83.5kg, DROP, 760mm

Backfill

3.4

Bentonite Seal

W.L. in
Standpipe at
Elev. 71.11
Jan. 5, 1988

1 : 26

CHECKED *AC*

Golder Associates


SAMPLER HAMMER 63.5kg DROP 760mm


PENETRATION TEST HAMMER 83.5kg DROP 780mm

1 : 25

CHECKED 

Golder Associates

| | | | | | | | | | | | | | | | |
|-------------------------------------|---|---|---|--|----------|---|---------------------------|--------------------------------------|------------------------|----------------------------|---|--------------|--|---|--|
| RECORD OF BOREHOLE 46 | | | | | | | | | | | | SHEET 2 of 2 | |  | |
| LOCATION See Figure 2 | | | | BORING DATE Dec.10,1987 | | | | DATUM GEODETIC | | | | | | | |
| SAMPLER HAMMER: 83.5kg, DROP: 780mm | | | | PENETRATION TEST HAMMER: 83.5kg, DROP: 780mm | | | | | | | | | | | |
| DEPTH SCALE METRES | BORING METHOD | SOIL PROFILE | | SAMPLES | | DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m | | HYDRAULIC CONDUCTIVITY, k, CM/SEC | | ADDITIONAL LAB. TESTING | PIEZOMETER OR STANDPIPE INSTALLATION | | | | |
| | | DESCRIPTION | STRATA PLOT ELEV. DEPTH (M) | NUMBER | TYPE | BLOWS/0.3m | SHEAR STRENGTH Cu, kPa | nat.V.- + Q.- rem.V.- @ U.- | WATER CONTENT, PERCENT | | | | | | |
| 5 | Power Auger 200mm Diam (Hollow Stem) | Hole Continued | 67.88 | | | | | | | | | | | | |
| | | Stiff grey SILTY CLAY, occasional thin sand seam | 6.00 | 7 | 50 DO | 2 | | + | | | | Backfill | | | |
| | | End of Hole | 67.10 5.78 | | | | | + | | | | | | | |
| 6 | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | W.L in Standpipe at Elev. 70.66 Jan. 8, 1988 | | | | |
| 9 | | | | | | | | | | | | | | | |
| 10 | | | | | | | | | | | | | | | |
| DEPTH SCALE | | | | | | LOGGED S.Leighton | | | | | | | | | |
| 1 : 25 | | | | Golder Associates | | CHECKED AC | | | | | | | | | |



APPENDIX C

Montreal Road Interchange
Relevant Borehole Logs by Others
Record of Boreholes 15-1 and 15-2
Figure C1

| G. C. McROSTIE CONSULTING CIVIL ENGINEERS OTTAWA CANADA | | | | SOIL PROFILE AND SUMMARY OF LABORATORY TESTS | | | |
|---|--------------------------------------|------------------|---|--|-----------|---------------------------------------|----------------------------|
| ELEVATION OF GROUND SURFACE (ZERO DEPTH) <u>183.6</u> | | | | HOLE NO. <u>1</u> | | | |
| REMARKS <u>Ceodetic datum</u> | | | | BORINGS BY <u>M^c Rostie</u> TESTING BY <u>M^c Rostie</u> DATE <u>9 Jan 56</u> | | | |
| UNCONFINED COMPRESSIVE STRENGTH KIPS/FT ² | STANDARD PENETRATION BLOWS/FT. | SAMPLE NUMBER | DESCRIPTION OF SOIL | DEPTH IN FEET | ELEVATION | PENETRATION TEST | |
| | | | | | | LB. HAMMER INCH DROP | NO CASING INCH DIA. ROD |
| GROUND SURFACE | | | | | | | |
| 3.17 | | 1 | Firm slightly fissured brownish grey clay 7.5 | 0 | 183.6 | Groundwater at surface | |
| 1.73 | | 2 | | 10 | | | |
| 1.73 | | 3 | | 20 | | | |
| 1.8 | | 4 | Medium | 30 | | | |
| 2.16 | | 5 | | 40 | | | |
| 1.94 | | 6 | Soft | 50 | 133.6 | | |
| 1.73 | | 7 | | 60 | | | |
| 1.8 | | 8 | gray | 70 | | | |
| 1.59 | | 9 | | 80 | | | |
| 1.73 | | 10 | clay | 90 | | | |
| 2.16 | | 11 | | 100 | 85.6 | | |
| 1.8 | | 12 | | 110 | | | |
| 1.94 | | 13 | | 120 | | | |
| 1.73 | | 14 | | 130 | | | |
| 1.8 | | 15 | | 140 | | | |
| 1.59 | | 16 | | 150 | 55.6 | | |
| 1.73 | | 17 | | | | | |
| 2.16 | | 18 | | | | | |
| 2.16 | | 19 | | | | | |
| 2.16 | | 20 | | | | | |
| | | | | | | 100 lb hammer 30 in drop 14" E rod | |
| | | | | | | % WATER CONTENT PLATE <u>2</u> | |

| G. C. McROSTIE CONSULTING CIVIL ENGINEERS OTTAWA CANADA | | | | SOIL PROFILE AND SUMMARY OF LABORATORY TESTS | | | |
|---|--------------------------------------|------------------|---|---|-----------|---------------------------------------|----------------------------|
| ELEVATION OF GROUND SURFACE (ZERO DEPTH) <u>186.04</u> | | | | HOLE NO. <u>2</u> | | | |
| REMARKS <u>Ceodetic survey</u> | | | | BORINGS BY <u>M^c Rostie</u> TESTING BY <u>M^c Rostie</u> DATE <u>12 Jan 56</u> | | | |
| UNCONFINED COMPRESSIVE STRENGTH KIPS/FT ² | STANDARD PENETRATION BLOWS/FT. | SAMPLE NUMBER | DESCRIPTION OF SOIL | DEPTH IN FEET | ELEVATION | PENETRATION TEST | |
| | | | | | | LB. HAMMER INCH DROP | NO CASING INCH DIA. ROD |
| GROUND SURFACE | | | | | | | |
| 3.17 | | 1 | Firm slightly fissured brownish grey clay 7.5 | 0 | 186.04 | Groundwater at surface | |
| 1.73 | | 2 | | 10 | | | |
| 1.73 | | 3 | | 20 | | | |
| 1.8 | | 4 | | 30 | | | |
| 2.16 | | 5 | Medium, soft | 40 | | | |
| 1.94 | | 6 | | 50 | 136.04 | | |
| 1.73 | | 7 | gray | 60 | | | |
| 1.8 | | 8 | | 70 | | | |
| 1.59 | | 9 | clay | 80 | | | |
| 1.73 | | 10 | | 90 | | | |
| 2.16 | | 11 | | 100 | 86.04 | | |
| 1.8 | | 12 | | 110 | | | |
| 1.94 | | 13 | | 120 | | | |
| 1.73 | | 14 | | 130 | | | |
| 1.8 | | 15 | | 140 | | | |
| 1.59 | | 16 | | 150 | | | |
| 1.73 | | 17 | | | | | |
| 2.16 | | 18 | | | | | |
| 2.16 | | 19 | | | | | |
| 2.16 | | 20 | | | | | |
| | | | | | | 100 lb hammer 30 in drop 14" E rod | |
| | | | | | | % WATER CONTENT PLATE <u>3</u> | |

RECORD OF BOREHOLE No 1

W P 911-73-00 LOCATION Sta. 16+276.0; 0/S 21.00 m Lt. of Hwy 17 W.B.L. ORIGINATED BY M.M.
DIST 9 HWY 17 W.B.L. BOREHOLE TYPE Hollow Stem Augers & Cone Test & Washboring COMPILED BY M.M.
DATUM Geodetic DATE April 17-19, 1978 CHECKED BY R.S.

| SOIL PROFILE | | SAMPLES | | | GROUND WATER CONDITIONS | ELEVATION m | DYNAMIC CONE PENETRATION RESISTANCE PLOT | | | | PLASTIC LIMIT W _p | NATURAL MOISTURE CONTENT W | LIQUID LIMIT W _L | UNIT WEIGHT γ | REMARKS & GRAIN SIZE DISTRIBUTION (%) |
|---------------|--|---------------|--------|------|----------------------------|----------------|---|----|----|----|------------------------------------|-------------------------------------|-----------------------------------|---------------------|---|
| ELEV DEPTH | DESCRIPTION | STRAT PLOT | NUMBER | TYPE | | | 20 | 40 | 60 | 80 | | | | | |
| 44.33 | Ground Level | | | | | | | | | | | | | | |
| 0.00 | Silty Clay Rust Mottled and Oxidized Very Stiff | | 1 | SS | 4 | | | | | | | | | | |
| | | | 2 | TW | PH | | | | | | | | | | |
| 41.33 | | | 3 | TW | PH | | | | | | | | | | |
| 3.00 | Stiff | | 4 | TW | PH | | | | | | | | | | |
| | Stiff to Very Stiff | | 5 | TW | PH | | | | | | | | | | |
| | Sensitive Clay | | 6 | TW | PH | | | | | | | | | | |
| | Gray | | 7 | TW | PH | | | | | | | | | | |
| | | | 8 | SS | 3 | | | | | | | | | | |
| | | | 9 | TW | PH | | | | | | | | | | |
| | | | 10 | SS | 10 | | | | | | | | | | |
| | | | 11 | TW | PH | | | | | | | | | | |
| | With Inclusions or Pockets of Organics | | 12 | SS | 7 | | | | | | | | | | |
| | | | 13 | TW | PH | | | | | | | | | | |
| | | | 14 | SS | 10 | | | | | | | | | | |
| 14.33 | | | | | | | | | | | | | | | |
| 30.00 | | | | | | | | | | | | | | | |

Continued

+3, x5: Numbers refer to
Sensitivity

20
15 5 (%) STRAIN AT FAILURE
10

RECORD OF BOREHOLE No 1 Continued

W P 911-73-00 LOCATION Sta. 16+276.0; 0/S 21.00 m Lt. of Hwy 17 W.B.L. ORIGINATED BY M.M.
DIST 9 HWY 17 W.B.L. BOREHOLE TYPE Hollow Stem Augers, Cone Test & Washboring COMPILED BY J.A.
DATUM Geodetic DATE April 17-19, 1978 CHECKED BY R.S.


| SOIL PROFILE | | SAMPLES | | | GROUND WATER CONDITIONS | ELEVATION m | DYNAMIC CONE PENETRATION RESISTANCE PLOT | | | | PLASTIC LIMIT W _p | NATURAL MOISTURE CONTENT W | LIQUID LIMIT W _L | UNIT WEIGHT γ | REMARKS & GRAIN SIZE DISTRIBUTION (%) |
|---------------|--|---------------|--------|-----------|----------------------------|----------------|---|----|----|----|------------------------------------|-------------------------------------|-----------------------------------|---------------------|---|
| ELEV DEPTH | DESCRIPTION | STRAT PLOT | NUMBER | TYPE | | | 20 | 40 | 60 | 80 | | | | | |
| 14.33 | continued | | | | | | | | | | | | | | |
| 30.00 | Sensitive Clay | | | | | | | | | | | | | | |
| 11.72 | | | | | | | | | | | | | | | |
| 32.61 | Heterogeneous Mixture Clayey Silt, Sand and Gravel, Hard | | 15 | SS | 17 | | | | | | | | | | |
| 10.19 | | | | | | | | | | | | | | | |
| 34.14 | Heterogeneous Mixture Silt, Sand & Gravel With Cobbles, Diameter 50-150 mm, Every 450 mm, Very Dense (Glacial Till) | | | | | | | | | | | | | | |
| 5.32 | | | | | | | | | | | | | | | |
| 39.01 | Black Shale Bedrock Sound | | 17 | RC BXL | REC 100% ROD 90% | | | | | | | | | | |
| 3.30 | | | | | | | | | | | | | | | |
| 41.03 | | | | | | | | | | | | | | | |

+3, x5: Numbers refer to
Sensitivity

20
15 5 (%) STRAIN AT FAILURE
10

PLASTICITY CHART

FIGURE C1



| Legend | Borehole | Sample | Depth (m) | LL % | PL % | PI % |
|--------|----------|--------|-----------|------|------|------|
| ● | 15-1 | 9 | 9.1 - 9.8 | 52.8 | 26.9 | 26.0 |
| ⊠ | 15-2 | 5 | 4.6 - 5.2 | 55.5 | 26.5 | 29.1 |



geotechnical
environmental
hydrogeology
materials testing & inspection